

SAFETY DATA SHEET

Version 6.15 Revision Date 11/27/2024 Print Date 11/28/2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Peracetic acid solution

Product Number : 269336 Brand : SIGALD

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

Uses advised against : This product is not intended for consumer use.

The product is being supplied under the TSCA R&D Exemption (40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by

MilliporeSigma.

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.

3050 SPRUCE ST ST. LOUIS MO 63103 UNITED STATES

Telephone : +1 314 771-5765 Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-

527-3887 CHEMTREC (International) 24

Hours/day; 7 Days/week

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 3), H226 Organic peroxides (Type D), H242 Corrosive to Metals (Category 1), H290

SIGALD - 269336

Page 1 of 20



Acute toxicity, Oral (Category 4), H302 Skin corrosion (Category 1), H314 Serious eye damage (Category 1), H318

Pictogram

Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335

Short-term (acute) aquatic hazard (Category 1), H400 Long-term (chronic) aquatic hazard (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Signal Word	Danger			
Hazard Statements				
H226	Flammable liquid and vapor.			

H226 Flammable liquid and vapor.
H242 Heating may cause a fire.
H290 May be corrosive to metals.
H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary Statements	
P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No
	smoking.
P220	Keep/Store away from clothing/ combustible materials.
P233	Keep container tightly closed.
P234	Keep only in original container.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing mist or vapors.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.

P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel

unwell. Rinse mouth.

P301 + P330 + P331

P303 + P361 + P353

IF SWALLOWED: Call a Folson CENTERy doctor in you reel unwell. Rinse mouth.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P310

IF INHALED: Remove person to fresh air and keep comfortable

for breathing. Immediately call a POISON CENTER/ doctor.

P305 + P351 + P338 +

P310

Finalled. Remove person to fresh all and keep connortable for breathing. Immediately call a POISON CENTER/ doctor.

IF INALED. Remove person to fresh all and keep connortable for breathing. Immediately call a POISON CENTER/ doctor.

P310

Remove contact lenses, if present and easy to do. Continue

rinsing. Immediately call a POISON CENTER/ doctor.

P363 Wash contaminated clothing before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant

SIGALD - 269336



	foam to extinguish.
P390	Absorb spillage to prevent material damage.
P391	Collect spillage.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P406	Store in corrosive resistant container with a resistant inner
	liner.
P410	Protect from sunlight.
P420	Store away from other materials.
P501	Dispose of contents/ container to an approved waste disposal
	plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Synonyms : Peroxyacetic acid

 $\begin{array}{lll} Formula & : & C_2H_4O_3 \\ Molecular \ weight & : & 76.05 \ g/mol \end{array}$

Component		Classification	Concentration
acetic acid			
CAS-No. EC-No. Index-No. Registration number	64-19-7 200-580-7 607-002-00-6 01-2119475328-30- XXXX	Flam. Liq. 3; Skin Corr. 1A; Eye Dam. 1; H226, H314, H318 Concentration limits: >= 90 %: Skin Corr. 1A, H314; 25 - < 90 %: Skin Corr. 1B, H314; 10 - < 25 %: Skin Irrit. 2, H315; 10 - < 25 %: Eye Irrit. 2, H319; > 80 %: Flam. Liq. 3, H226;	>= 30 - < 50 %
Peracetic acid			
CAS-No. EC-No. Index-No.	79-21-0 201-186-8 607-094-00-8	Flam. Liq. 3; Org. Perox. D; Acute Tox. 4; Skin Corr. 1A; Eye Dam. 1; Aquatic Acute 1; Aquatic Chronic 1; H226, H242, H302, H332, H312, H314, H318, H400, H410 Concentration limits: >= 1 %: STOT SE 3, H335; M-Factor - Aquatic Acute: 10	>= 30 - < 50 %

SIGALD - 269336 Page 3 of 20



Hydrogen Peroxide			
CAS-No. EC-No. Index-No. Registration number	7722-84-1 231-765-0 008-003-00-9 01-2119485845-22- xxxx	Ox. Liq. 1; Acute Tox. 4; Skin Corr. 1A; Eye Dam. 1; STOT SE 3; Aquatic Acute 2; Aquatic Chronic 3; H271, H302, H332, H314, H318, H335, H401, H412 Concentration limits: >= 70 %: Ox. Liq. 1, H271; 50 - < 70 %: Ox. Liq. 2, H272; >= 70 %: Skin Corr. 1A, H314; 50 - < 70 %: Skin Corr. 1B, H314; 35 - < 50 %: Skin Irrit. 2, H315; 8 - < 50 %: Eye Dam. 1, H318; 5 - < 8 %: Eye Irrit. 2, H319; >= 35 %: STOT SE 3, H335; > 40 - < 50 %: Ox. Liq. 3, H272;	>= 5 - < 8 %
sulphuric acid			
CAS-No. EC-No. Index-No. Registration number	7664-93-9 231-639-5 016-020-00-8 01-2119458838-20- XXXX	Met. Corr. 1; Skin Corr. 1A; Eye Dam. 1; H290, H314, H318 Concentration limits: >= 0.3 %: Met. Corr. 1, H290; >= 15 %: Skin Corr. 1A, H314; 5 - < 15 %: Skin Irrit. 2, H315; 5 - < 15 %: Eye Irrit. 2, H319;	>= 1 - < 5 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

SIGALD - 269336

Page 4 of 20



In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation). Call a physician immediately. Do not attempt to neutralise.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water Foam Carbon dioxide (CO2) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Sulfur oxides

Combustible.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air at elevated temperatures.

Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

SIGALD - 269336

Page 5 of 20



6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent and neutralising material (e.g. Chemizorb® H⁺, Merck Art. No. 101595). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Protect against light. No metal containers.

Tightly closed. Separately or together with other organic peroxides only and away from sources of ignition and heat.

Storage stabilityRecommended storage temperature 2 - 8 °C

Storage class

Storage class (TRGS 510): 5.2: Organic peroxides and self-reacting hazardous materials

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

SIGALD - 269336



Component	CAS-No.	Value	Control parameters	Basis
acetic acid	64-19-7	TWA	10 ppm	USA. ACGIH Threshold Limit Values (TLV)
		STEL	15 ppm	USA. ACGIH Threshold Limit Values (TLV)
		TWA	10 ppm 25 mg/m3	USA. NIOSH Recommended Exposure Limits
		ST	15 ppm 37 mg/m3	USA. NIOSH Recommended Exposure Limits
		TWA	10 ppm 25 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		PEL	10 ppm 25 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		С	40 ppm	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		STEL	15 ppm 37 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
Peracetic acid	79-21-0	STEL	0.4 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Not classifiable as a human carcinogen		
Hydrogen Peroxide	7722-84-1	TWA	1 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Confirmed animal carcinogen with unknown relevance to humans		

SIGALD - 269336 Page 7 of 20



		TWA	1 ppm 1.4 mg/m3	USA. NIOSH Recommended Exposure Limits
		TWA	1 ppm 1.4 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		PEL	1 ppm 1.4 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
sulphuric acid	7664-93-9	TWA	1 mg/m3	USA. NIOSH Recommended Exposure Limits
		TWA	0.2 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
		TWA	1 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		TWA	1 mg/m3	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
		PEL	0.1 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		STEL	3 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.3 mm Break through time: 480 min

Material tested:Butoject® (KCL 897 / Aldrich Z677647, Size M)

Splash contact

Material: Nature latex/chloroprene

SIGALD - 269336



Minimum layer thickness: 0.6 mm Break through time: 30 min

Material tested:Lapren® (KCL 706 / Aldrich Z677558, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail

sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

Recommended Filter type: Filter type ABEK

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

a) Appearance Form: liquid

Color: colorless

b) Odor pungent

c) Odor Threshold No data available

d) pH

Melting point/ range: -44 °C (-47 °F) e) Melting

56 °C (133 °F)

point/freezing point

Initial boiling point 107 °C 225 °F at 1,013 hPa

and boiling range

h) Evaporation rate No data available

Flammability (solid, No data available

gas)

g) Flash point

Upper/lower No data available

flammability or

SIGALD - 269336

1 AilliPORE

explosive limits

k) Vapor pressure 27 hPa at 25 °C (77 °F)

I) Vapor density No data available

m) Density 1.13 g/cm3 at 25 °C (77 °F)

Relative density No data available

n) Water solubility soluble

o) Partition coefficient: No data available

n-octanol/water

p) Autoignition 218 °C (424 °F)

temperature

q) Decomposition No data available

temperature

r) Viscosity No data available

s) Explosive properties Not classified as explosive.

t) Oxidizing properties none

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapor/air-mixtures are explosive at intense warming.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Heating.

10.5 Incompatible materials

Strong reducing agents, Strong bases, Heavy metal saltsMetals

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Mixture

Acute toxicity

Oral: No data available

SIGALD - 269336

Millipore SigMa Inhalation: No data available

Dermal: No data available

No data available

Skin corrosion/irritation Remarks: No data available

Serious eye damage/eye irritation

Remarks: No data available

Remarks: Mixture causes serious eye damage.

Risk of blindness!

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available No data available

Specific target organ toxicity - single exposure

Remarks: No data available

Mixture may cause respiratory irritation.

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., spasm, inflammation and edema of the larynx, spasm, inflammation and edema of the bronchi, pneumonitis, pulmonary edema, burning sensation, Cough, wheezing, laryngitis, Shortness of breath, Headache, Nausea Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

Stomach - Irregularities - Based on Human Evidence

SIGALD - 269336

Page 11 of 20



Components

acetic acid

Acute toxicity

LD50 Oral - Rat - 3,310 mg/kg

Remarks: (RTECS)

LC50 Inhalation - Mouse - 4 h - 2,819 mg/l - vapor

Remarks: (RTECS)

Dermal: No data available

Skin corrosion/irritation

Skin - Rabbit

Result: Causes burns. - 4 h (OECD Test Guideline 404)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table

3.1/3.2)

Serious eye damage/eye irritation

Eves - Rabbit

Result: Causes burns. - 4 h (OECD Test Guideline 405)

Remarks: (IUCLID)

Remarks: Causes serious eye damage.

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

Test Type: Ames test

Test system: Salmonella typhimurium

Result: negative

Test Type: Mutagenicity (mammal cell test): chromosome aberration.

Test system: Chinese hamster ovary cells

Result: negative

Method: Mutagenicity (micronucleus test)
Species: Rat - male and female - Bone marrow

Result: negative

Carcinogenicity No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

SIGALD - 269336 Page 12 of 20

Peracetic acid

Acute toxicity

LD50 Oral - Rat - male and female - > 7.5 mg/kg

(OECD Test Guideline 401)

LC50 Inhalation - Rat - male and female - 4 h - 186 mg/m3 - aerosol

Remarks: (ECHA)

LD50 Dermal - Rabbit - male and female - > 17.8 mg/kg

(US-EPA)

LD50 Intravenous - Mouse - male - 212 mg/kg

Remarks: (ECHA)

Skin corrosion/irritation

Skin - Rabbit

Result: Causes severe burns. - 4 h

(OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit Result: Corrosive

(US-EPA)

Respiratory or skin sensitization

Maximization Test - Guinea pig

Result: negative

(Regulation (EC) No. 440/2008, Annex, B.6)

Germ cell mutagenicity

Test Type: reverse mutation assay Test system: S. typhimurium

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster fibroblasts

Result: negative

Test Type: Chromosome aberration test in vitro Test system: Chinese hamster fibroblasts

Result: negative

Method: OECD Test Guideline 474

Species: Mouse - male and female - Red blood cells (erythrocytes)

Result: negative

Method: OECD Test Guideline 486 Species: Rat - male - Liver cells

Result: negative **Carcinogenicity**

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

operates as MilliporeSigma in the US and Canada

SIGALD - 269336

AilliPDRE

Page 13 of 20

Specific target organ toxicity - repeated exposure

Aspiration hazard

No data available

Hydrogen Peroxide

Acute toxicity

LD50 Oral - Rat - female - 693.7 mg/kg

(OECD Test Guideline 401)

Acute toxicity estimate Inhalation - 4 h - 11.1 mg/l - vapor

(Expert judgment)

LD50 Dermal - Rabbit - male and female - > 2,000 mg/kg

(US-EPA)

No data available

Skin corrosion/irritation

Remarks: Causes severe burns.

Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Serious eye damage/eye irritation

Remarks: Causes serious eye damage.

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

Method: OECD Test Guideline 474

Species: Mouse - male and female - Bone marrow

Result: negative

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Inhalation - May cause respiratory irritation. - Respiratory Tract

Specific target organ toxicity - repeated exposure

Aspiration hazard

No data available

sulphuric acid

Acute toxicity

LD50 Oral - Rat - male and female - 2,140 mg/kg

Remarks: (ECHA)

Inhalation: No data available Dermal: No data available

Skin corrosion/irritation

Skin - Rabbit

Result: Extremely corrosive and destructive to tissue.

SIGALD - 269336

Page 14 of 20

Remarks: (IUCLID)

Serious eye damage/eye irritation Remarks: Causes serious eye damage.

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

Test Type: Ames test

Test system: Salmonella typhimurium

Result: negative Remarks: (HSDB) Carcinogenicity No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

SECTION 12: Ecological information

12.1 Toxicity

Mixture

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

No data available

Components

acetic acid

Toxicity to fish semi-static test LC50 - Oncorhynchus mykiss (rainbow trout) -

SIGALD - 269336

Page 15 of 20



> 1,000 mg/l - 96 h (OECD Test Guideline 203)

Toxicity to daphnia and other aquatic

static test EC50 - Daphnia magna (Water flea) - > 1,000 mg/l

invertebrates (OECD Test Guideline 202)

Toxicity to algae static test EC50 - Skeletonema costatum - > 1,000 mg/l - 72 h

(ISO 10253)

Toxicity to bacteria EC5 - Pseudomonas putida - 2,850 mg/l - 16 h

Remarks: neutral

(maximum permissible toxic concentration)

(Lit.)

microtox test EC50 - Photobacterium phosphoreum - 11 mg/l -

Remarks: (IUCLID)

Peracetic acid

Toxicity to fish semi-static test LC50 - Oncorhynchus mykiss (rainbow trout) -

0.53 mg/l - 96 h

(OECD Test Guideline 203)

Toxicity to daphnia and other aquatic invertebrates

static test EC50 - Daphnia magna (Water flea) - 0.73 mg/l - 48

(OECD Test Guideline 202)

Toxicity to algae static test ErC50 - Pseudokirchneriella subcapitata (green

algae) - 0.16 mg/l - 72 h

(US-EPA)

static test NOEC - Pseudokirchneriella subcapitata (green algae)

- 0.061 mg/l - 72 h

(US-EPA)

Toxicity to bacteria static test EC50 - activated sludge - 5.1 mg/l - 3 h

(OECD Test Guideline 209)

static test NOEC - activated sludge - 16.7 mg/l - 3 h

(OECD Test Guideline 209)

Toxicity to daphnia

semi-static test NOEC - Daphnia magna (Water flea) - 0.012

and other aquatic mg/l - 21 d

invertebrates(Chronic (OECD Test Guideline 211)

toxicity)

Hydrogen Peroxide

Toxicity to fish semi-static test LC50 - Pimephales promelas (fathead minnow)

- 16.4 mg/l - 96 h

(US-EPA)

Toxicity to daphnia

semi-static test LC50 - Daphnia pulex (Water flea) - 2.4 mg/l -

and other aquatic

48 h

SIGALD - 269336

Page 16 of 20

invertebrates (US-EPA)

static test ErC50 - Skeletonema costatum (marine diatom) -Toxicity to algae

> 1.38 mg/l - 72 h Remarks: (ECHA)

static test NOEC - Skeletonema costatum (marine diatom) -

0.63 mg/l - 72 h Remarks: (ECHA)

static test EC50 - activated sludge - 466 mg/l - 30 min Toxicity to bacteria

(OECD Test Guideline 209)

static test EC50 - activated sludge - > 1,000 mg/l - 3 h

flow-through test NOEC - Daphnia magna (Water flea) - 0.63

static test EC50 - Daphnia magna (Water flea) - > 100 mg/l -

(OECD Test Guideline 209)

Toxicity to daphnia

and other aquatic

mg/l - 21 d

invertebrates(Chronic Remarks: (ECHA)

sulphuric acid

toxicity)

Toxicity to daphnia

and other aquatic

invertebrates (OECD Test Guideline 202)

static test ErC50 - Desmodesmus subspicatus (green algae) - > Toxicity to algae

100 mg/l - 72 h

(OECD Test Guideline 201)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

SECTION 14: Transport information

DOT (US)

UN number: 3109 Class: 5.2 (8)

Proper shipping name: Organic peroxide type F, liquid (Peroxyacetic acid)

SIGALD - 269336

Page 17 of 20



Reportable Quantity (RQ):

Poison Inhalation Hazard: No

IMDG

UN number: 3109 Class: 5.2 (8) EMS-No: F-J, S-R

Proper shipping name: ORGANIC PEROXIDE TYPE F, LIQUID (PEROXYACETIC ACID, TYPE F)

IATA

UN number: 3109 Class: 5.2 (HEAT, 8)

Proper shipping name: Organic peroxide type F, liquid (Peroxyacetic acid)

Special Provisions: "Keep away from heat" label required.

SECTION 15: Regulatory information

CERCLA Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component	Calculated product
		RQ (lbs)	RQ (lbs)
Peracetic acid	79-21-0	500	1408

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

Components	CAS-No.	Component TPQ (lbs)
Peracetic acid	79-21-0	500
Hydrogen Peroxide	7722-84-1	1000
sulphuric acid	7664-93-9	1000

SARA 311/312 : Fire Hazard

Hazards Reactivity Hazard

Acute Health Hazard Chronic Health Hazard

SARA 313 : The following components are subject to reporting

levels established by SARA Title III, Section 313:

Peracetic acid 79-21-0 >= 30 - < 50 %

sulphuric acid 7664-93-9 >= 1 - < 5 %

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B). This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

The following chemical(s) are listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F):

Peracetic acid 79-21-0 >= 30 - < 50 %

SIGALD - 269336 Page 18 of 20

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489):

acetic acid 64-19-7 >= 30 - < 50 %

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

acetic acid 64-19-7 >= 30 - < 50 % sulphuric acid 7664-93-9 >= 1 - < 5 %

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

acetic acid 64-19-7 >= 30 - < 50 % sulphuric acid 7664-93-9 >= 1 - < 5 %

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

acetic acid	64-19-7
Peracetic acid	79-21-0
water	7732-18-5
Hydrogen Peroxide	7722-84-1
sulphuric acid	7664-93-9

Pennsylvania Right To Know

acetic acid	64-19-7
Peracetic acid	79-21-0
Hydrogen Peroxide	7722-84-1
sulphuric acid	7664-93-9

Maine Chemicals of High Concern

water	7732-18-5

Vermont Chemicals of High Concern

water	7732-18-5

Washington Chemicals of High Concern

water	7732-18-5
water	//32-18-

California Prop. 65

WARNING: This product can expose you to chemicals including sulphuric acid, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SIGALD - 269336

Page 19 of 20



SECTION 16: Other information

Further information

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.15 Revision Date: 11/27/2024 Print Date: 11/28/2024

SIGALD - 269336 Page 20 of 20

