

SAFETY DATA SHEET

Version 6.6
Revision Date 03/02/2024
Print Date 05/26/2024**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifiers**

Product name : Butyl glycidyl ether

Product Number : 377031
Brand : Aldrich
Index-No. : 603-039-00-7
CAS-No. : 2426-08-6

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

Uses advised against : The product is being supplied under the TSCA R&D Exemption (40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by MilliporeSigma.

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 SPRUCE ST
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-527-3887 CHEMTREC (International) 24 Hours/day; 7 Days/week

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Flammable liquids (Category 3), H226
Acute toxicity, Oral (Category 4), H302
Acute toxicity, Inhalation (Category 3), H331

Skin corrosion (Category 1B), H314
 Serious eye damage (Category 1), H318
 Skin sensitization (Category 1), H317
 Germ cell mutagenicity (Category 2), H341
 Carcinogenicity (Category 1B), H350
 Reproductive toxicity (Category 2), H361
 Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335
 Short-term (acute) aquatic hazard (Category 2), H401
 Long-term (chronic) aquatic hazard (Category 2), H411

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal Word

Danger

Hazard Statements

H226	Flammable liquid and vapor.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H361	Suspected of damaging fertility or the unborn child.
H411	Toxic to aquatic life with long lasting effects.

Precautionary Statements

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing mist or vapors.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing must not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P312 + P330	IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.
P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P310	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
P305 + P351 + P338 + P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P363	Wash contaminated clothing before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391	Collect spillage.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : Butyl-2,3-epoxypropylether
(Butoxymethyl)oxirane
Araldite RD-1

Formula : C₇H₁₄O₂
Molecular weight : 130.18 g/mol
CAS-No. : 2426-08-6
EC-No. : 219-376-4
Index-No. : 603-039-00-7

Component	Classification	Concentration
butyl 2,3-epoxypropyl ether		
	Flam. Liq. 3; Acute Tox. 4; Acute Tox. 3; Skin Irrit. 2; Eye Dam. 1; Skin Sens. 1; Muta. 2; Carc. 2; Repr. 2; STOT SE 3; Aquatic Acute 2; Aquatic Chronic 2; H226, H302, H331, H315, H318, H317, H341, H351, H361, H335, H401, H411	<= 100 %
1-chloro-2,3-epoxypropane		
	Flam. Liq. 3; Acute Tox. 3; Skin Corr. 1B; Eye Dam. 1; Skin Sens. 1; Carc. 1B;	>= 5 - < 10 %

Aldrich - 377031

Page 3 of 13

	Aquatic Acute 3; H226, H301, H331, H311, H314, H318, H317, H350, H402	
--	---	--

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation). Call a physician immediately. Do not attempt to neutralise.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Foam Carbon dioxide (CO₂) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Hydrogen chloride gas

Combustible.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air at elevated temperatures.

Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorized persons.

Air, light, and moisture sensitive.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Ingredients with workplace control parameters**

Component	CAS-No.	Value	Control parameters	Basis
butyl 2,3-epoxypropyl ether	2426-08-6	TWA	3 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Dermal Sensitization Danger of cutaneous absorption		
		C	5.6 ppm 30 mg/m ³	USA. NIOSH Recommended Exposure Limits
		TWA	50 ppm 270 mg/m ³	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		PEL	25 ppm 135 mg/m ³	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
1-chloro-2,3-epoxypropane	106-89-8	TWA	0.5 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Confirmed animal carcinogen with unknown relevance to humans Danger of cutaneous absorption		
		Potential Occupational Carcinogen		
		TWA	5 ppm 19 mg/m ³	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		Skin designation		
		PEL	0.05 ppm 0.19 mg/m ³	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		Skin		

8.2 Exposure controls**Appropriate engineering controls**

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Splash contact

Material: butyl-rubber

Minimum layer thickness: 0.3 mm

Break through time: 60 min

Material tested: Butoject® (KCL 897 / Aldrich Z677647, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

Recommended Filter type: Filter type ABEK

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- | | |
|-------------------|---|
| a) Appearance | Form: clear, liquid
Color: colorless |
| b) Odor | No data available |
| c) Odor Threshold | No data available |

d) pH	No data available
e) Melting point/freezing point	No data available
f) Initial boiling point and boiling range	164 - 166 °C 327 - 331 °F - lit.
g) Flash point	54 °C (129 °F) - closed cup
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	No data available
k) Vapor pressure	3.99 hPa at 20 °C (68 °F)
l) Vapor density	No data available
m) Density	0.91 g/mL at 25 °C (77 °F) - lit.
Relative density	No data available
n) Water solubility	No data available
o) Partition coefficient: n-octanol/water	No data available
p) Autoignition temperature	No data available
q) Decomposition temperature	No data available
r) Viscosity	No data available
s) Explosive properties	No data available
t) Oxidizing properties	none

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapor/air-mixtures are explosive at intense warming.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Heating.

Aldrich - 377031

Page 8 of 13

10.5 Incompatible materials

Strong oxidizing agents

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Acute toxicity estimate Oral - 1,103 mg/kg

(Calculation method)

LD50 Oral - Mouse - male - 1,530 mg/kg (butyl 2,3-epoxypropyl ether)

Remarks: (ECHA)

Inhalation: No data available

Acute toxicity estimate Inhalation - 4 h - 6.19 mg/l - vapor (Calculation method)

LC50 Inhalation - Rat - male - 4 h - 6.93 mg/l - vapor

(butyl 2,3-epoxypropyl ether)

Remarks: (ECHA)

Dermal: No data available

Acute toxicity estimate Dermal - > 5,000 mg/kg

(Calculation method)

LD50 Dermal - Rat - > 2,150 mg/kg (butyl 2,3-epoxypropyl ether)

Remarks: (RTECS)

No data available

Skin corrosion/irritation

Skin - Rabbit (butyl 2,3-epoxypropyl ether)

Result: Skin irritation - 24 h

Remarks: (RTECS)

Serious eye damage/eye irritation

Eyes - Rabbit (butyl 2,3-epoxypropyl ether)

Result: Severe eye irritation - 24 h

Remarks: (RTECS)

Respiratory or skin sensitization

May cause allergic skin reaction. Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2) (butyl 2,3-epoxypropyl ether)

Germ cell mutagenicity

Suspected of causing genetic defects. (butyl 2,3-epoxypropyl ether)

Test Type: unscheduled DNA synthesis assay

(butyl 2,3-epoxypropyl ether)

Test system: mammalian cells

Metabolic activation: without metabolic activation

Result: negative

Remarks: (ECHA)

Test Type: Ames test

(butyl 2,3-epoxypropyl ether)
Test system: *S. typhimurium*
Metabolic activation: with and without metabolic activation
Result: negative
Remarks: (ECHA)
(butyl 2,3-epoxypropyl ether)
Test Type: Chromosome aberration test in vitro
Species: Rat
Cell type: Bone marrow
Application Route: Intraperitoneal

Result: positive
Remarks: (ECHA)

Carcinogenicity

Suspected of causing cancer. (butyl 2,3-epoxypropyl ether)

IARC: 2A - Group 2A: Probably carcinogenic to humans (1-chloro-2,3-epoxypropane)

IARC: 2B - Group 2B: Possibly carcinogenic to humans (butyl 2,3-epoxypropyl ether)

NTP: RAHC - Reasonably anticipated to be a human carcinogen (1-chloro-2,3-epoxypropane)

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

Suspected of damaging the unborn child. (butyl 2,3-epoxypropyl ether)

No data available

Suspected of damaging fertility. (butyl 2,3-epoxypropyl ether)

Specific target organ toxicity - single exposure

Inhalation - May cause respiratory irritation. - Nasal inner lining (butyl 2,3-epoxypropyl ether)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

RTECS: TX4200000

Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., spasm, inflammation and edema of the larynx, spasm, inflammation and edema of the bronchi, pneumonitis, pulmonary edema, burning sensation, Cough, wheezing, laryngitis, Shortness of breath, Headache, Nausea, Vomiting (butyl 2,3-epoxypropyl ether)

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated. (butyl 2,3-epoxypropyl ether)

Stomach - Irregularities - Based on Human Evidence

Stomach - Irregularities - Based on Human Evidence
(butyl 2,3-epoxypropyl ether)

Aldrich - 377031

Page 10 of 13

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish	semi-static test LC50 - Oncorhynchus mykiss (rainbow trout) - 65 mg/l - 96 h (butyl 2,3-epoxypropyl ether) Remarks: (ECHA)
Toxicity to daphnia and other aquatic invertebrates	static test EC50 - Daphnia magna (Water flea) - 9.2 mg/l - 48 h (butyl 2,3-epoxypropyl ether) Remarks: (ECHA)
Toxicity to algae	static test ErC50 - Pseudokirchneriella subcapitata - 35 mg/l - 96 h (butyl 2,3-epoxypropyl ether) Remarks: (ECHA)

12.2 Persistence and degradability

Biodegradability	aerobic - Exposure time 28 d (butyl 2,3-epoxypropyl ether) Result: 25 % - Not readily biodegradable. (OECD Test Guideline 301B)
------------------	---

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

SECTION 14: Transport information**DOT (US)**

UN number: 3271 Class: 3 Packing group: III
Proper shipping name: Ethers, n.o.s.
Reportable Quantity (RQ): 2000 lbs
Poison Inhalation Hazard: No

IMDG

UN number: 3271 Class: 3 Packing group: III EMS-No: F-E, S-D
Proper shipping name: ETHERS, N.O.S. (butyl 2,3-epoxypropyl ether)

IATA

UN number: 3271 Class: 3 Packing group: III
Proper shipping name: Ethers, n.o.s. (butyl 2,3-epoxypropyl ether)

SECTION 15: Regulatory information**SARA 302 Components**

1-chloro-2,3-epoxypropane	CAS-No. 106-89-8	Revision Date 2008-11-03
---------------------------	---------------------	-----------------------------

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

1-chloro-2,3-epoxypropane	CAS-No. 106-89-8	Revision Date 2008-11-03
---------------------------	---------------------	-----------------------------

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

butyl 2,3-epoxypropyl ether	CAS-No. 2426-08-6	Revision Date 1993-02-16
1-chloro-2,3-epoxypropane	106-89-8	2008-11-03

Pennsylvania Right To Know Components

Aldrich - 377031

Page 12 of 13

butyl 2,3-epoxypropyl ether	CAS-No. 2426-08-6	Revision Date 1993-02-16
-----------------------------	----------------------	-----------------------------

1-chloro-2,3-epoxypropane	106-89-8	2008-11-03
---------------------------	----------	------------

California Prop. 65 Components

, which is/are known to the State of California to cause cancer, andbutyl 2,3-epoxypropyl ether	CAS-No. 2426-08-6	Revision Date 2023-04-21
---	----------------------	-----------------------------

1-chloro-2,3-epoxypropane	106-89-8	2007-09-28
---------------------------	----------	------------

, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov .1-chloro-2,3-epoxypropane	CAS-No. 106-89-8	Revision Date 2007-09-28
---	---------------------	-----------------------------

SECTION 16: Other information

Further information

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.6

Revision Date: 03/02/2024

Print Date: 05/26/2024