

SAFETY DATA SHEET

Version 6.7
Revision Date 10/19/2022
Print Date 11/26/2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : 1,2-Dichloroethane
Product Number : 02562
Brand : Sigma-Aldrich
Index-No. : 602-012-00-7
CAS-No. : 107-06-2

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 SPRUCE ST
ST. LOUIS MO 63103
UNITED STATES
Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-
527-3887 CHEMTREC (International) 24
Hours/day; 7 Days/week

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225
Acute toxicity, Oral (Category 4), H302
Acute toxicity, Inhalation (Category 3), H331
Skin irritation (Category 2), H315
Eye irritation (Category 2A), H319
Carcinogenicity (Category 1B), H350
Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335
Aspiration hazard (Category 1), H304

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal Word

Danger

Hazard statement(s)

H225	Highly flammable liquid and vapor.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H350	May cause cancer.

Precautionary statement(s)

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing mist or vapors.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P311	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P331	Do NOT induce vomiting.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : Ethylene dichloride
Ethylene chloride

Formula : C₂H₄Cl₂
Molecular weight : 98.96 g/mol
CAS-No. : 107-06-2
EC-No. : 203-458-1
Index-No. : 602-012-00-7

Component	Classification	Concentration
1,2-Dichloroethane	Flam. Liq. 2; Acute Tox. 4; Acute Tox. 3; Skin Irrit. 2; Eye Irrit. 2A; Carc. 1B; STOT SE 3; Asp. Tox. 1; H225, H302, H331, H315, H319, H350, H335, H304	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: caution if victim vomits. Risk of aspiration! Keep airways free. Pulmonary failure possible after aspiration of vomit. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water Foam Carbon dioxide (CO₂) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Hydrogen chloride gas

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorized persons.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
1,2-Dichloroethane	107-06-2	TWA	10 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Not classifiable as a human carcinogen		
		ST	2 ppm 8 mg/m ³	USA. NIOSH Recommended Exposure Limits
		Potential Occupational Carcinogen		
		TWA	1 ppm 4 mg/m ³	USA. NIOSH Recommended Exposure Limits
		Potential Occupational Carcinogen		

		TWA	50 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		CEIL	100 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		Peak	200 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		PEL	1 ppm 4 mg/m ³	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		C	200 ppm	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		STEL	2 ppm 8 mg/m ³	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: Viton®

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact

Material: Chloroprene

Minimum layer thickness: 0.65 mm

Break through time: 10 min

Material tested: KCL 720 Camapren®

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance	Form: viscous liquid Color: colorless
b) Odor	of solvents
c) Odor Threshold	3 ppm
d) pH	No data available
e) Melting point/freezing point	Melting point/range: -35 °C (-31 °F) - lit.
f) Initial boiling point and boiling range	83 °C 181 °F - lit.
g) Flash point	ca.13 °C (55 °F) - closed cup - DIN 51755 Part 1
h) Evaporation rate	4.1
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	Upper explosion limit: 15.9 %(V) Lower explosion limit: 6 %(V)
k) Vapor pressure	102 hPa at 25 °C (77 °F) 87 hPa at 20 °C(68 °F)
l) Vapor density	4.1 at 20 °C(68 °F)
m) Density	1.256 g/mL at 25 °C (77 °F) - lit.
Relative density	No data available
n) Water solubility	7.9 g/l at 25 °C (77 °F) - OECD Test Guideline 105 - soluble
o) Partition coefficient: n-octanol/water	log Pow: 1.45 at 20 °C (68 °F) - Bioaccumulation is not expected.
p) Autoignition temperature	440 °C (824 °F) at 1,013 hPa - DIN 51794
q) Decomposition temperature	300 °C (572 °F) -
r) Viscosity	No data available
s) Explosive properties	No data available
t) Oxidizing properties	none

9.2 Other safety information

Sigma-Aldrich - 02562

Page 7 of 13

Surface tension	32.45 mN/m at 20 °C (68 °F)
Relative vapor density	4.1 at 20 °C (68 °F)

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapors may form explosive mixture with air.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Exothermic reaction with:

Alkaline earth metals

alkali amides

Nitric acid

nitrogen oxides

Oxidizing agents

Chlorine

powdered magnesium

Zinc

Risk of explosion with:

Alkali metals

powdered aluminium

Powdered metals

Potassium

nitrogen dioxide

10.4 Conditions to avoid

Warming.

10.5 Incompatible materials

various plastics, Light metals, Iron

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male - 770 mg/kg

(OECD Test Guideline 401)

LC50 Inhalation - Rat - male and female - 4 h - 7.8 mg/l - vapor

(OECD Test Guideline 403)
LD50 Dermal - Rabbit - male - 4,890 mg/kg
(OECD Test Guideline 402)

Skin corrosion/irritation

Skin - Rabbit
Result: irritating
(OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit
Result: Eye irritation
(OECD Test Guideline 405)

Respiratory or skin sensitization

Local lymph node assay (LLNA) - Mouse
Result: negative
(OECD Test Guideline 429)

Germ cell mutagenicity

Test Type: Ames test
Test system: *S. typhimurium*
Metabolic activation: with and without metabolic activation
Result: positive
Remarks: (ECHA)
Test Type: Ames test
Test system: *Escherichia coli*
Metabolic activation: without metabolic activation
Method: OECD Test Guideline 471
Result: positive
Test Type: In vitro mammalian cell gene mutation test
Test system: human lymphoblastoid cells
Metabolic activation: without metabolic activation
Method: OECD Test Guideline 476
Result: positive
Test Type: In vitro mammalian cell gene mutation test
Test system: human lymphoblastoid cells
Metabolic activation: without metabolic activation
Result: positive
Remarks: (ECHA)
Test Type: Mutagenicity (mammal cell test): chromosome aberration.
Test system: Chinese hamster lung cells
Metabolic activation: with and without metabolic activation
Result: positive
Remarks: (ECHA)
Test Type: unscheduled DNA synthesis assay
Test system: rat hepatocytes
Metabolic activation: without metabolic activation
Method: OECD Test Guideline 482
Result: positive

Test Type: Micronucleus test
Species: Mouse

Application Route: Intraperitoneal
Method: OECD Test Guideline 474
Result: negative

Test Type: Mutagenicity (mammal cell test): micronucleus.
Species: Mouse
Cell type: Red blood cells (erythrocytes)
Application Route: Oral
Method: OECD Test Guideline 474
Result: negative

Test Type: sister chromatid exchange assay
Species: Rat
Cell type: mammary gland
Application Route: inhalation (vapor)

Result: negative
Remarks: (ECHA)

Species: Drosophila melanogaster
Cell type: sperm
Application Route: Inhalation
Method: OECD Test Guideline 477
Result: positive

Test Type: Transgenic rodent somatic cell gene mutation assay
Species: Mouse

Application Route: Intraperitoneal

Result: negative
Remarks: (ECHA)

Carcinogenicity

Presumed to have carcinogenic potential for humans

IARC: 2B - Group 2B: Possibly carcinogenic to humans (1,2-Dichloroethane)

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

Aspiration may cause pulmonary edema and pneumonitis.

11.2 Additional Information

Repeated dose toxicity - Rat - male and female - Oral - 90 d - NOAEL (No observed adverse effect level) - 37.5 mg/kg

Remarks: Subchronic toxicity

Repeated dose toxicity - Mouse - male and female - Inhalation - 104 Weeks

RTECS: KI0525000

Acts as a simple asphyxiant by displacing air., anesthetic effects, Difficulty in breathing, Headache, Dizziness, Prolonged or repeated contact with skin may cause:, defatting, Dermatitis, Contact with eyes can cause:, Redness, Blurred vision, Provokes tears., Effects due to ingestion may include:, Gastrointestinal discomfort, Central nervous system depression, Paresthesia., Drowsiness, Convulsions, Conjunctivitis., Pulmonary edema. Effects may be delayed., Irregular breathing., Stomach/intestinal disorders, Nausea, Vomiting, Increased liver enzymes., Weakness, Heavy or prolonged skin exposure may result in the absorption of harmful amounts of material.

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Pancreas. -

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish	flow-through test LC50 - Pimephales promelas (fathead minnow) - 136 mg/l - 96 h (OECD Test Guideline 203)
Toxicity to daphnia and other aquatic invertebrates	static test EC50 - Daphnia magna (Water flea) - 160 mg/l - 48 h Remarks: (in soft water) (IUCLID)
Toxicity to algae	static test EC50 - Desmodesmus subspicatus (green algae) - 166 mg/l - 72 h (OECD Test Guideline 201)
Toxicity to bacteria	static test EC50 - activated sludge - 35,500 mg/l - 3 h (OECD Test Guideline 209)
Toxicity to daphnia and other aquatic invertebrates(Chronic toxicity)	static test NOEC - Daphnia magna (Water flea) - 11 mg/l - 28 d Remarks: (ECHA)

12.2 Persistence and degradability

Biodegradability	aerobic - Exposure time 20 d Result: > 90 % - Inherently biodegradable. Remarks: (ECHA)
------------------	---

12.3 Bioaccumulative potential

Bioaccumulation	Lepomis macrochirus - 14 d at 16 °C - 0.957 mg/l(1,2-Dichloroethane)
	Bioconcentration factor (BCF): 2

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

SECTION 14: Transport information

DOT (US)

UN number: 1184 Class: 3 (6.1) Packing group: II
Proper shipping name: Ethylene dichloride
Reportable Quantity (RQ): 100 lbs
Reportable Quantity (RQ): 100 lbs
Poison Inhalation Hazard: No

IMDG

UN number: 1184 Class: 3 (6.1) Packing group: II EMS-No: F-E, S-D
Proper shipping name: ETHYLENE DICHLORIDE

IATA

UN number: 1184 Class: 3 (6.1) Packing group: II
Proper shipping name: Ethylene dichloride

SECTION 15: Regulatory information

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

	CAS-No.	Revision Date
1,2-Dichloroethane	107-06-2	2020-07-14

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Reportable Quantity : D028 lbs

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

SECTION 16: Other information

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.7

Revision Date: 10/19/2022

Print Date: 11/26/2022