

## SAFETY DATA SHEET

Version 6.11  
Revision Date 03/02/2024  
Print Date 06/22/2024**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifiers**

Product name : (±)-Propylene oxide

Product Number : 110205

Brand : Aldrich

Index-No. : 603-055-00-4

CAS-No. : 75-56-9

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Identified uses : Laboratory chemicals, Synthesis of substances

Uses advised against : The product is being supplied under the TSCA R&D Exemption (40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by MilliporeSigma.

**1.3 Details of the supplier of the safety data sheet**

Company : Sigma-Aldrich Inc.  
3050 SPRUCE ST  
ST. LOUIS MO 63103  
UNITED STATES

Telephone : +1 314 771-5765

Fax : +1 800 325-5052

**1.4 Emergency telephone**

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-527-3887 CHEMTREC (International) 24 Hours/day; 7 Days/week

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Flammable liquids (Category 1), H224  
Acute toxicity, Oral (Category 4), H302  
Acute toxicity, Inhalation (Category 3), H331

Acute toxicity, Dermal (Category 3), H311  
 Eye irritation (Category 2A), H319  
 Germ cell mutagenicity (Category 1B), H340  
 Carcinogenicity (Category 1B), H350  
 Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335  
 Short-term (acute) aquatic hazard (Category 3), H402

For the full text of the H-Statements mentioned in this Section, see Section 16.

## 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal Word

Danger

Hazard Statements

H224	Extremely flammable liquid and vapor.
H302	Harmful if swallowed.
H311 + H331	Toxic in contact with skin or if inhaled.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H340	May cause genetic defects.
H350	May cause cancer.
H402	Harmful to aquatic life.

Precautionary Statements

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing mist or vapors.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P312 + P330	IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P311	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.

P337 + P313	If eye irritation persists: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

---

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Synonyms	: (±)-Methyloxirane 1,2-Epoxypropane
Formula	: C <sub>3</sub> H <sub>6</sub> O
Molecular weight	: 58.08 g/mol
CAS-No.	: 75-56-9
EC-No.	: 200-879-2
Index-No.	: 603-055-00-4

Component	Classification	Concentration
<b>propylene oxide</b>		
	Flam. Liq. 1; Acute Tox. 4; Acute Tox. 3; Eye Irrit. 2A; Muta. 1B; Carc. 1B; STOT SE 3; Aquatic Acute 3; H224, H302, H331, H311, H319, H340, H350, H335, H402	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

---

## SECTION 4: First aid measures

### 4.1 Description of first-aid measures

#### General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

#### If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

**In case of skin contact**

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

**In case of eye contact**

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

**If swallowed**

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

**4.2 Most important symptoms and effects, both acute and delayed**

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

**4.3 Indication of any immediate medical attention and special treatment needed**

No data available

---

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO<sub>2</sub>) Foam Dry powder

**Unsuitable extinguishing media**

For this substance/mixture no limitations of extinguishing agents are given.

**5.2 Special hazards arising from the substance or mixture**

Carbon oxides

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

**5.3 Advice for firefighters**

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

**5.4 Further information**

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

---

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

## **6.2 Environmental precautions**

Do not let product enter drains. Risk of explosion.

## **6.3 Methods and materials for containment and cleaning up**

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

## **6.4 Reference to other sections**

For disposal see section 13.

---

## **SECTION 7: Handling and storage**

### **7.1 Precautions for safe handling**

#### **Advice on safe handling**

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

#### **Advice on protection against fire and explosion**

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

#### **Hygiene measures**

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

### **7.2 Conditions for safe storage, including any incompatibilities**

#### **Storage conditions**

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorized persons.

#### **Storage stability** Recommended storage temperature

2 - 8 °C

Over time, pressure may increase causing containers to burst. Handle and open container with care. Heat sensitive. Cool to 0°C before opening.

#### **Storage class**

Storage class (TRGS 510): 3: Flammable liquids

### **7.3 Specific end use(s)**

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

---

## **SECTION 8: Exposure controls/personal protection**

### **8.1 Control parameters**

#### **Ingredients with workplace control parameters**

Component	CAS-No.	Value	Control parameters	Basis
propylene oxide	75-56-9	TWA	2 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Dermal Sensitization Confirmed animal carcinogen with unknown relevance to humans		
		Potential Occupational Carcinogen		
		TWA	100 ppm 240 mg/m <sup>3</sup>	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		PEL	2 ppm 4.75 mg/m <sup>3</sup>	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

## 8.2 Exposure controls

### Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

### Personal protective equipment

#### Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

#### Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

Splash contact

Material: butyl-rubber

Minimum layer thickness: 0.7 mm

Break through time: 30 min

Material tested: Butoject® (KCL 898)

#### Body Protection

Flame retardant antistatic protective clothing.

#### Respiratory protection

Recommended Filter type: Filter type AX

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

## Control of environmental exposure

Do not let product enter drains. Risk of explosion.

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

a) Appearance	Form: clear, liquid Color: colorless
b) Odor	sweet, ether-like
c) Odor Threshold	No data available
d) pH	No data available
e) Melting point/freezing point	Melting point/range: -112 °C (-170 °F) - lit.
f) Initial boiling point and boiling range	34 °C 93 °F - lit.
g) Flash point	-38 °C (-36 °F) - Equilibrium method - closed cup
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	Upper explosion limit: 36 - 45 %(V) Lower explosion limit: 1.9 %(V)
k) Vapor pressure	2,028.5 hPa at 55 °C (131 °F)
l) Vapor density	2.01 - (Air = 1.0)
m) Density	0.83 g/mL at 25 °C (77 °F) - lit.
Relative density	0.8320 °C - Regulation (EC) No. 440/2008, Annex, A.3
n) Water solubility	425 g/l at 20 °C (68 °F) - OECD Test Guideline 105
o) Partition coefficient: n-octanol/water	log Pow: < 1 at 20 °C (68 °F) - Bioaccumulation is not expected.
p) Autoignition temperature	> 400 °C (> 752 °F) at 1,005 - 1,018 hPa - Tested according to Directive 92/69/EEC.
q) Decomposition temperature	No data available
r) Viscosity	0.44 mm <sup>2</sup> /s at 0 °C (32 °F) - OECD Test Guideline 114 - 0.37 mm <sup>2</sup> /s at 20 °C (68 °F) - OECD Test Guideline 114 -
s) Explosive properties	No data available
t) Oxidizing properties	none

#### 9.2 Other safety information

Surface tension	71.5 mN/m at 1.06g/l at 21 °C (70 °F) - Regulation (EC) No. 440/2008, Annex, A.5
-----------------	--

Relative vapor density                      2.01 - (Air = 1.0)

---

## **SECTION 10: Stability and reactivity**

### **10.1 Reactivity**

Vapors may form explosive mixture with air.

### **10.2 Chemical stability**

The product is chemically stable under standard ambient conditions (room temperature) .

### **10.3 Possibility of hazardous reactions**

Risk of ignition or formation of inflammable gases or vapours with:

Hydrogen fluoride

Oxidizing agents

Nitric acid

Risk of explosion with:

polymerisation initiators

Oxygen

Exothermic reaction with:

Strong oxidizing agents

Ammonia

halogens

alkali hydroxides

polymerization

alkalines

Amines

metallic oxides

metallic chlorides

chlorosulfonic acid

Hydrogen chloride gas

fuming sulfuric acid

aluminium chloride

acids

### **10.4 Conditions to avoid**

Heat.

Warming.

### **10.5 Incompatible materials**

No data available

### **10.6 Hazardous decomposition products**

In the event of fire: see section 5



---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

LD50 Oral - Rat - male and female - 382 - 587 mg/kg  
(OECD Test Guideline 401)

LC50 Inhalation - Rat - male and female - 4 h - 9.95 mg/l - vapor

(OECD Test Guideline 403)

LD50 Dermal - Rabbit - 950 mg/kg

Remarks: (ECHA)

#### Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 4 h

(OECD Test Guideline 404)

#### Serious eye damage/eye irritation

Eyes - Rabbit

Result: Severe irritations

(Draize Test)

Remarks: (RTECS)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

#### Respiratory or skin sensitization

Split adjuvant test - Guinea pig

Result: negative

Remarks: (ECHA)

#### Germ cell mutagenicity

May cause genetic defects.

Test Type: Ames test

Test system: Escherichia coli/Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: positive

Test Type: In vitro mammalian cell gene mutation test

Test system: Mouse lymphoma test

Metabolic activation: without metabolic activation

Method: OECD Test Guideline 476

Result: positive

Test Type: Mutagenicity (mammal cell test): chromosome aberration.

Metabolic activation: without metabolic activation

Method: OECD Test Guideline 473

Result: positive

Test Type: Mutagenicity (mammal cell test): micronucleus.

Species: Rat

Cell type: Red blood cells (erythrocytes)

Application Route: inhalation (vapor)

Method: OECD Test Guideline 474

Result: negative

Test Type: Mutagenicity (mammal cell test): chromosome aberration.  
Species: Rat

Application Route: inhalation (vapor)  
Method: OECD Test Guideline 475  
Result: negative

### **Carcinogenicity**

Presumed to have carcinogenic potential for humans

IARC: 2B - Group 2B: Possibly carcinogenic to humans (propylene oxide)  
NTP: RAHC - Reasonably anticipated to be a human carcinogen (propylene oxide)  
OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

### **Reproductive toxicity**

No data available

### **Specific target organ toxicity - single exposure**

Inhalation - May cause respiratory irritation. - Respiratory system  
Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

### **Specific target organ toxicity - repeated exposure**

No data available

### **Aspiration hazard**

No data available

## **11.2 Additional Information**

RTECS: TZ2975000  
burning sensation, Cough, wheezing, laryngitis, Shortness of breath, Headache, Nausea, Vomiting, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence

Stomach - Irregularities - Based on Human Evidence

---

## **SECTION 12: Ecological information**

### **12.1 Toxicity**

Toxicity to fish	static test LC50 - Oncorhynchus mykiss (rainbow trout) - 52 mg/l - 96 h (US-EPA)
Toxicity to daphnia and other aquatic invertebrates	static test EC50 - Daphnia magna (Water flea) - 350 mg/l - 48 h (US-EPA)
Toxicity to algae	static test ErC50 - Pseudokirchneriella subcapitata (green algae) - 240 mg/l - 96 h (US-EPA)

Toxicity to fish(Chronic toxicity) EC50 - Poecilia reticulata (guppy) - 31.9 mg/l - 14 d  
Remarks: (Lit.)

### 12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 28 d  
Result: 96 % - Readily biodegradable.  
(OECD Test Guideline 301C)

### 12.3 Bioaccumulative potential

Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected.

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

### 12.6 Endocrine disrupting properties

No data available

### 12.7 Other adverse effects

Stability in water - 15.7 yr  
Remarks: reaction with hydroxyl radicals(calculated)  
- ca.11 d  
Remarks: Hydrolysis

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

---

## SECTION 14: Transport information

### DOT (US)

UN number: 1280 Class: 3 Packing group: I  
Proper shipping name: Propylene oxide  
Reportable Quantity (RQ): 100 lbs  
Poison Inhalation Hazard: No

### IMDG

UN number: 1280 Class: 3 Packing group: I EMS-No: F-E, S-D  
Aldrich - 110205

Page 11 of 13

Proper shipping name: PROPYLENE OXIDE

**IATA**

UN number: 1280 Class: 3

Packing group: I

Proper shipping name: Propylene oxide

---

**SECTION 15: Regulatory information**

**SARA 302 Components**

propylene oxide

CAS-No.  
75-56-9

Revision Date  
2008-11-03

**SARA 313 Components**

The following components are subject to reporting levels established by SARA Title III, Section 313:

propylene oxide

CAS-No.  
75-56-9

Revision Date  
2008-11-03

**SARA 311/312 Hazards**

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

**Massachusetts Right To Know Components**

propylene oxide

CAS-No.  
75-56-9

Revision Date  
2008-11-03

**Pennsylvania Right To Know Components**

propylene oxide

CAS-No.  
75-56-9

Revision Date  
2008-11-03

**California Prop. 65 Components**

, which is/are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).propylene oxide

CAS-No.  
75-56-9

Revision Date  
2007-09-28

---

**SECTION 16: Other information**

**Further information**

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See [www.sigma-aldrich.com](http://www.sigma-aldrich.com) and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact [mlsbranding@sial.com](mailto:mlsbranding@sial.com).

Version: 6.11

Revision Date: 03/02/2024

Print Date: 06/22/2024