

SAFETY DATA SHEET

Version 8.11
Revision Date 03/02/2024
Print Date 04/13/2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Potassium hydroxide solution
in ethanol c(KOH) = 0.5 mol/l (0.5 N)
Titripur® Reag. Ph Eur

Product Number : 1.09114
Catalogue No. : 109114
Brand : Millipore

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Reagent for analysis
Uses advised against : The product is being supplied under the TSCA R&D Exemption (40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by MilliporeSigma.

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 SPRUCE ST
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-
527-3887 CHEMTREC (International) 24
Hours/day; 7 Days/week

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225
Corrosive to Metals (Category 1), H290
Skin corrosion (Category 1B), H314

Millipore - 1.09114

Page 1 of 15

Serious eye damage (Category 1), H318

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal Word

Danger

Hazard Statements

H225

Highly flammable liquid and vapor.

H290

May be corrosive to metals.

H314

Causes severe skin burns and eye damage.

Precautionary Statements

P210

Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.

P233

Keep container tightly closed.

P234

Keep only in original container.

P240

Ground/bond container and receiving equipment.

P241

Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242

Use only non-sparking tools.

P243

Take precautionary measures against static discharge.

P264

Wash skin thoroughly after handling.

P280

Wear protective gloves/ protective clothing/ eye protection/ face protection.

P301 + P330 + P331

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P310

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.

P305 + P351 + P338 +

IF IN EYES: Rinse cautiously with water for several minutes.

P310

Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P363

Wash contaminated clothing before reuse.

P370 + P378

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

P390

Absorb spillage to prevent material damage.

P403 + P235

Store in a well-ventilated place. Keep cool.

P405

Store locked up.

P406

Store in corrosive resistant container with a resistant inner liner.

P501

Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Millipore - 1.09114

Page 2 of 15

The life science business of Merck KGaA, Darmstadt, Germany operates as MilliporeSigma in the US and Canada

Component		Classification	Concentration
ethanol			
CAS-No.	64-17-5	Flam. Liq. 2; Eye Irrit. 2A; H225, H319 Concentration limits: >= 50 %: Eye Irrit. 2A, H319;	>= 70 - < 90 %
EC-No.	200-578-6		
Index-No.	603-002-00-5		
Registration number	01-2119457610-43-XXXX		
caustic potash			
CAS-No.	1310-58-3	Met. Corr. 1; Acute Tox. 4; Skin Corr. 1A; Eye Dam. 1; Aquatic Acute 3; H290, H302, H314, H318, H402 Concentration limits: >= 0.5 %: Met. Corr. 1, H290; >= 5 %: Skin Corr. 1A, H314; 2 - < 5 %: Skin Corr. 1B, H314; 0.5 - < 2 %: Skin Irrit. 2, H315; 0.5 - < 2 %: Eye Irrit. 2, H319;	>= 2 - < 5 %
EC-No.	215-181-3		
Index-No.	019-002-00-8		
Registration number	01-2119487136-33-XXXX		

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation). Call a physician immediately. Do not attempt to neutralise.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂) Dry powder Foam

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Potassium oxides

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent and neutralising material (e.g. Chemizorb® OH⁻, Merck Art. No. 101596). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

No metal containers.

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Recommended storage temperature see product label.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
ethanol	64-17-5	TWA	1,000 ppm 1,900 mg/m ³	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		STEL	1,000 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Confirmed animal carcinogen with unknown relevance to humans		

		TWA	1,000 ppm 1,900 mg/m ³	USA. NIOSH Recommended Exposure Limits
		PEL	1,000 ppm 1,900 mg/m ³	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
caustic potash	1310-58-3	C	2 mg/m ³	USA. ACGIH Threshold Limit Values (TLV)
		C	2 mg/m ³	USA. NIOSH Recommended Exposure Limits
		C	2 mg/m ³	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Butoject® (KCL 898)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.40 mm

Break through time: 120 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

Recommended Filter type: Filter A-(P2)

Millipore - 1.09114

Page 6 of 15

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented. required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance	Form: liquid Color: light yellow
b) Odor	of ethanol
c) Odor Threshold	No data available
d) pH	ca.14 at 20 °C (68 °F)
e) Melting point/freezing point	Melting point: -114.5 °C (-174.1 °F) - (ethanol)
f) Initial boiling point and boiling range	78.3 °C 172.9 °F at 1,013 hPa - (ethanol)
g) Flash point	12 °C (54 °F) - c.c. - (ethanol)
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	Upper explosion limit: 15.0 %(V) - (ethanol) Lower explosion limit: 3.5 %(V) - (ethanol)
k) Vapor pressure	59 hPa at 20 °C (68 °F) - (ethanol)
l) Vapor density	1.6 - (ethanol)
m) Density	0.85 g/cm ³ at 20 °C (68 °F)
Relative density	No data available
n) Water solubility	soluble
o) Partition coefficient: n-octanol/water	No data available
p) Autoignition temperature	No data available
q) Decomposition temperature	No data available
r) Viscosity	No data available

- s) Explosive properties Not classified as explosive.
- t) Oxidizing properties none

9.2 Other safety information

Relative vapor density 1.6 - (ethanol)

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapors may form explosive mixture with air.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Risk of explosion/exothermic reaction with:

hydrogen peroxide
perchlorates
perchloric acid
Nitric acid
mercury(II) nitrate
permanganic acid
Nitriles
peroxi compounds
Strong oxidizing agents
nitrosyl compounds
Peroxides
sodium
Potassium
halogen oxides
calcium hypochlorite
nitrogen dioxide
metallic oxides
uranium hexafluoride
iodides
Chlorine
Alkali metals
Alkaline earth metals
alkali oxides
Ethylene oxide
silver
with
Nitric acid
silver compounds
with
Ammonia
potassium permanganate
with

conc. sulfuric acid
Risk of ignition or formation of inflammable gases or vapours with:
halogen-halogen compounds
chromium(VI) oxide
chromyl chloride
Fluorine
hydrides
Oxides of phosphorus
platinum
Nitric acid
with
potassium permanganate

10.4 Conditions to avoid

Warming.
Keep away from open flames, hot surfaces and sources of ignition.
Warming.

10.5 Incompatible materials

animal/vegetable tissues, glass, various plastics, various metals, various alloysMetals

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Mixture

Acute toxicity

Acute toxicity estimate Oral - > 5,000 mg/kg
(Calculation method)

Symptoms: If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the esophagus and the stomach.

Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages:, damage of respiratory tract

Dermal: No data available

Skin corrosion/irritation

Remarks: Mixture causes burns.

Serious eye damage/eye irritation

Remarks: Mixture causes serious eye damage.
Risk of blindness!

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is

Millipore - 1.09114

Page 9 of 15

identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

Components

ethanol

Acute toxicity

LD50 Oral - Rat - male and female - 10,470 mg/kg

(OECD Test Guideline 401)

LC50 Inhalation - Rat - male and female - 4 h - 124.7 mg/l - vapor

(OECD Test Guideline 403)

Dermal: No data available

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 24 h

(OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Causes serious eye irritation.

(OECD Test Guideline 405)

Respiratory or skin sensitization

Maximization Test - Guinea pig

Result: negative

(OECD Test Guideline 406)

Remarks: (in analogy to similar products)

The value is given in analogy to the following substances: Methanol

Germ cell mutagenicity

Test Type: Ames test

Test system: Salmonella typhimurium

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Result: negative

Method: OECD Test Guideline 478

Species: Mouse - male

Result: Positive results were obtained in some in vivo tests.

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure**Aspiration hazard**

No data available

caustic potash**Acute toxicity**

LD50 Oral - Rat - male - 333 mg/kg

(OECD Test Guideline 425)

Symptoms: If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the esophagus and the stomach.

Inhalation: Corrosive to respiratory system.

Symptoms: burns of mucous membranes, Cough, Shortness of breath, Possible damages:, damage of respiratory tract

Dermal: No data available

Skin corrosion/irritation

Skin - Rabbit

Result: Causes burns.

Remarks: (IUCLID)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Causes serious eye damage.

(OECD Test Guideline 405)

Remarks: Causes serious eye damage.

Respiratory or skin sensitization

Sensitisation test: - Guinea pig

Result: negative

Remarks: (IUCLID)

Germ cell mutagenicity

Test Type: Ames test

Test system: S. typhimurium

Result: negative

Remarks: (ECHA)

Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Result: negative

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Acute oral toxicity - If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the esophagus and the stomach.

Acute inhalation toxicity - burns of mucous membranes, Cough, Shortness of breath, Possible damages:, damage of respiratory tract

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

SECTION 12: Ecological information**12.1 Toxicity****Mixture**

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Discharge into the environment must be avoided.

Components**ethanol**

Toxicity to fish

flow-through test LC50 - Pimephales promelas (fathead minnow) - 15,300 mg/l - 96 h

	(US-EPA)
Toxicity to daphnia and other aquatic invertebrates	static test LC50 - Ceriodaphnia dubia (water flea) - 5,012 mg/l - 48 h Remarks: (ECHA)
Toxicity to algae	static test ErC50 - Chlorella vulgaris (Fresh water algae) - 275 mg/l - 72 h (OECD Test Guideline 201)
Toxicity to bacteria	static test IC50 - activated sludge - > 1,000 mg/l - 3 h (OECD Test Guideline 209)
Toxicity to fish(Chronic toxicity)	semi-static test NOEC - Danio rerio (zebra fish) - 250 mg/l - 120 h Remarks: (ECHA)
Toxicity to daphnia and other aquatic invertebrates(Chronic toxicity)	semi-static test NOEC - Daphnia magna (Water flea) - 9.6 mg/l - 9 d Remarks: (ECHA)
caustic potash	
Toxicity to fish	static test LC50 - Gambusia affinis (Mosquito fish) - 80 mg/l - 96 h Remarks: (ECOTOX Database)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

SECTION 14: Transport information

DOT (US)

UN number: 2924 Class: 3 (8) Packing group: II
 Proper shipping name: Flammable liquids, corrosive, n.o.s. (ethanol, Potassium hydroxide)
 Reportable Quantity (RQ):
 Poison Inhalation Hazard: No

Millipore - 1.09114

Page 13 of 15

IMDG

UN number: 2924 Class: 3 (8) Packing group: II EMS-No: F-E, S-C
 Proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, Potassium hydroxide)

IATA

UN number: 2924 Class: 3 (8) Packing group: II
 Proper shipping name: Flammable liquid, corrosive, n.o.s. (ethanol, Potassium hydroxide)

SECTION 15: Regulatory information**SARA 302 Components**

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Massachusetts Right To Know Components

	CAS-No.	Revision Date
ethanol	64-17-5	
	7732-18-5	
water		
	1310-58-3	1989-08-11
Potassium hydroxide		

Pennsylvania Right To Know Components

	CAS-No.	Revision Date
ethanol	64-17-5	
Potassium hydroxide	1310-58-3	1989-08-11

California Prop. 65 Components

	CAS-No.	Revision Date
, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov .ethanol	64-17-5	

SECTION 16: Other information**Further information**

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent

any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 8.11

Revision Date: 03/02/2024

Print Date: 04/13/2024