

SAFETY DATA SHEET

according to the OSHA
Hazard Communication Standard

Version 9.6
Revision Date 07/15/2026
Print Date 07/16/2026

SECTION 1. IDENTIFICATION

1.1 Product identifiers

Product name : Ethyllithium solution

Product Number : 561452
Brand : Aldrich

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

Restrictions on use : Not Available

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 SPRUCE ST
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone number

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-
527-3887 CHEMTREC (International) 24
Hours/day; 7 Days/week

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Hazards for the product as supplied

Flammable liquids : Category 2

Chemicals which, in
contact with water, emit
flammable gases : Category 2

Skin irritation	: Category 2
Eye irritation	: Category 2A
Germ cell mutagenicity	: Category 1B
Carcinogenicity	: Category 1A
Specific target organ toxicity - repeated exposure	: Category 1 (Blood)
Aspiration hazard	: Category 1
Short-term (acute) aquatic hazard	: Category 2
Long-term (chronic) aquatic hazard	: Category 2

Other hazards

None known.

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements :

- H225 Highly flammable liquid and vapour.
- H261 In contact with water releases flammable gases.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H340 May cause genetic defects.
- H350 May cause cancer.
- H372 Causes damage to organs (Blood) through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.

Precautionary statements :

Prevention:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
- P223 Do not allow contact with water.
- P231 + P232 Handle under inert gas. Protect from moisture.

P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P335 + P334 Brush off loose particles from skin. Immerse in cool water/ wrap in wet bandages.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391 Collect spillage.

Storage:

P402 + P404 Store in a dry place. Store in a closed container.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Aldrich - 561452

Page 3 of 22

CAS-No. : Not Assigned

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
benzene	71-43-2*	$\geq 70 - < 90$	-
Cyclohexane	110-82-7*	$\geq 10 - < 20$	-
Ethyllithium	811-49-4*	$\geq 1 - < 5$	-

* Indicates that the identifier is a CAS No.

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : Show this safety data sheet to the doctor in attendance.
- If inhaled : After inhalation: fresh air. Call in physician.
- In case of skin contact : In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.
- In case of eye contact : After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.
- If swallowed : After swallowing: caution if victim vomits. Risk of aspiration! Keep airways free. Pulmonary failure possible after aspiration of vomit. Call a physician immediately.
- Most important symptoms and effects, both acute and delayed : The most important known symptoms and effects are described in the labelling (see section 2 GHS label elements) and/or in section 11
- Protection of first-aiders : For personal protection see section 8.
- Notes to physician : No data available

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Carbon dioxide (CO₂)
Dry powder

Unsuitable extinguishing media : Water
Foam

Specific hazards during fire fighting : Combustible.

Pay attention to flashback.

Vapours are heavier than air and may spread along floors.

May not get in touch with: Water

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

Hazardous combustion products : Carbon oxides

Lithium oxides

Specific extinguishing methods : No data available

Further information : Remove container from danger zone and cool with water.
Prevent fire extinguishing water from contaminating surface water or the ground water system.

Special protective equipment for fire-fighters : Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, : Advice for non-emergency personnel:

Aldrich - 561452

Page 5 of 22

protective equipment and emergency procedures	Do not breathe vapours, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. Advice for emergency responders: Wear appropriate personal protective equipment, as indicated in Section 8.
---	---

Environmental precautions	: Do not let product enter drains. Risk of explosion.
---------------------------	--

Methods and materials for containment and cleaning up	: Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.
---	--

SECTION 7. HANDLING AND STORAGE

For precautions see section 2 GHS label elements

Advice on protection against fire and explosion	: Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.
---	--

Advice on safe handling	: Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols. Keep workplace dry. Do not allow product to come into contact with water.
-------------------------	---

Further information on storage conditions	: Tightly closed. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorised persons.
---	---

Materials to avoid	: Never allow product to get in contact with water during storage.
--------------------	--

Storage class	: 4.3, Hazardous materials, which set free flammable gases upon contact with water
---------------	--

Recommended storage temperature	: 36 - 46 °F / 2 - 8 °C
---------------------------------	-------------------------

Further information on	: Handle and store under inert gas.
------------------------	-------------------------------------

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
benzene	71-43-2	TWA	0.5 ppm	ACGIH
		STEL	2.5 ppm	ACGIH
		TWA	10 ppm	OSHA Z-2
		CEIL	25 ppm	OSHA Z-2
		Peak	50 ppm	OSHA Z-2
		TWA	0.1 ppm	NIOSH REL
		ST	1 ppm	NIOSH REL
Cyclohexane	110-82-7	TWA	100 ppm	ACGIH
		TWA	300 ppm 1,050 mg/m ³	NIOSH REL
		TWA	300 ppm 1,050 mg/m ³	OSHA Z-1

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Cyclohexane	110-82-7	1,2-Cyclohexanediol	Urine	End of shift at end of workweek	50 mg/g creatinine	ACGIH BEI

Engineering measures : No data available

Personal protective equipment

Respiratory protection : required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Recommended Filter type: : Filter type ABEK

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Hand protection

Remarks : required

Eye protection : Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).
Safety glasses

Skin and body protection : Flame retardant antistatic protective clothing.

Hygiene measures : Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : No data available

Odour : No data available

Odour Threshold : No data available
pH : No data available

Melting point : No data available

Boiling point/boiling range : No data available

Flash point : -17.00 °F / -27.22 °C
Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Flammability (liquids) : No data available

Burning rate : No data available

Self-ignition : The substance or mixture is not classified as pyrophoric.

Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available
Density	: 0.862 g/cm ³ (77 °F / 25 °C)
Water solubility	: No data available
Partition coefficient: n- octanol/water	: No data available
Autoignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Flow time	: No data available
Explosive properties	: Not classified as explosive.
Oxidizing properties	: none
Molecular weight	: 36.00 g/mol
Particle characteristics Particle size	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Vapours may form explosive mixture with air.
Chemical stability	: The product is chemically stable under standard ambient conditions (room temperature) .
Possibility of hazardous reactions	: No data available

Conditions to avoid	: Warming. Moisture.
Incompatible materials	: Bases Strong oxidizing agents acids Halogens Metallic salts
Hazardous decomposition products	: In the event of fire: see section 5

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Mixture

Acute toxicity

Oral: No data available

Acute toxicity estimate Oral - 3,411 mg/kg

(Calculation method)

Symptoms: Irritations of mucous membranes in the mouth, pharynx, oesophagus and gastrointestinal tract.

Inhalation: No data available

Symptoms: Possible symptoms:, mucosal irritations

Dermal: No data available

Acute toxicity estimate Dermal - > 5,000 mg/kg

(Calculation method)

Skin corrosion/irritation

Remarks: Mixture causes skin irritation.

Serious eye damage/eye irritation

Remarks: Mixture causes serious eye irritation.

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: 1 - Group 1: Carcinogenic to humans (benzene)

NTP: Known - Known to be human carcinogen (benzene)

OSHA: OSHA specifically regulated carcinogen (benzene)

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

Aspiration hazard, Aspiration may cause pulmonary oedema and pneumonitis.

11.2 Additional Information

Inhalation of high concentrations of benzene may have an initial stimulatory effect on the central nervous system characterized by exhilaration, nervous excitation and/or giddiness, depression, drowsiness, or fatigue. The victim may experience tightness in the chest, breathlessness, and loss of consciousness. Tremors, convulsions, and death due to respiratory paralysis or circulatory collapse can occur in a few minutes to several hours following severe exposures. Aspiration of small amounts of liquid immediately causes pulmonary edema and hemorrhage of pulmonary tissue. Direct skin contact may cause erythema. Repeated or prolonged skin contact may result in drying, scaling dermatitis, or development of secondary skin infections. The chief target organ is the hematopoietic system. Bleeding from the nose, gums, or mucous membranes and the development of purpuric spots, pancytopenia, leukopenia, thrombocytopenia, aplastic anemia, and leukemia may occur as the condition progresses. The bone marrow may appear normal, aplastic or hyperplastic, and may not correlate with peripheral blood-forming tissues. The onset of effects of prolonged benzene exposure may be delayed for many months or years after the actual exposure has ceased., Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., spasm, inflammation and edema of the larynx, spasm, inflammation and edema of the bronchi, pneumonitis, pulmonary edema, burning sensation, Cough, wheezing, laryngitis, Shortness of breath, Headache

Stomach - Irregularities - Based on Human Evidence

Components**benzene****Acute toxicity**

LD50 Oral - Rat - male - > 2,000 mg/kg

(OECD Test Guideline 401)

Symptoms: Nausea

LD50 Oral - Rat - male and female - 3,002 mg/kg

(OECD Test Guideline 401)

Symptoms: Risk of aspiration upon vomiting., Aspiration may cause pulmonary oedema and pneumonitis.

Inhalation: No data available

Symptoms: mucosal irritations

LD50 Dermal - Rabbit - 13,630 mg/kg

Remarks: (IUCLID)

No data available

Skin corrosion/irritation

Skin - Rabbit

Result: irritating

(OECD Test Guideline 404)

Remarks: (ECHA)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Irritating to eyes.

(OECD Test Guideline 405)

Remarks: (IUCLID)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Respiratory or skin sensitization

Maximisation Test - Guinea pig

Result: negative

(OECD Test Guideline 406)

Germ cell mutagenicity

May cause genetic defects.

Test Type: Ames test

Test system: Escherichia coli/Salmonella typhimurium

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Result: negative

Test Type: Chromosome aberration test in vitro

Test system: Chinese hamster lung cells

Result: negative

Method: OECD Test Guideline 474

Species: Mouse - male - Bone marrow

Result: positive

Carcinogenicity

May cause cancer. Positive evidence from human epidemiological studies.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Acute oral toxicity - Nausea

Acute oral toxicity - Risk of aspiration upon vomiting., Aspiration may cause pulmonary oedema and pneumonitis.

Acute inhalation toxicity - mucosal irritations

Specific target organ toxicity - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

- Blood

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Aspiration hazard

Aspiration may cause pulmonary oedema and pneumonitis.

Cyclohexane

Acute toxicity

LD50 Oral - Rat - male and female - > 5,000 mg/kg

(OECD Test Guideline 401)

Symptoms: gastric pain, Stomach/intestinal disorders

LC50 Inhalation - Rat - male and female - 4 h - > 32,800 mg/l - vapour

(OECD Test Guideline 403)

Symptoms: Possible damages:, Irritation symptoms in the respiratory tract.,

Inhalation may lead to the formation of oedemas in the respiratory tract.

LD50 Dermal - Rabbit - male and female - > 2,000 mg/kg

(OECD Test Guideline 402)

Skin corrosion/irritation

Remarks: Causes skin irritation.

Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Serious eye damage/eye irritation

Remarks: No data available

Respiratory or skin sensitization

Buehler Test - Guinea pig

Result: negative

(Regulation (EC) No. 440/2008, Annex, B.6)

Germ cell mutagenicity

Test Type: Ames test

Test system: Salmonella typhimurium

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: Mouse lymphoma test

Result: negative

Method: OECD Test Guideline 475

Species: Rat - male and female - Bone marrow

Result: negative

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Acute oral toxicity - gastric pain, Stomach/intestinal disorders

Acute inhalation toxicity - Possible damages:, Irritation symptoms in the respiratory tract., Inhalation may lead to the formation of oedemas in the respiratory tract.

Specific target organ toxicity - repeated exposure

Aspiration hazard

May be fatal if swallowed and enters airways. Aspiration hazard, Aspiration may cause pulmonary oedema and pneumonitis.

Ethyllithium

Acute toxicity

Oral: No data available
Inhalation: No data available
Dermal: No data available
No data available

Skin corrosion/irritation

Remarks: No data available

Serious eye damage/eye irritation

Remarks: No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available
No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

benzene:

Toxicity to fish	: LC50 (Oryzias latipes (Orange-red killifish)): > 100 mg/l End point: mortality Exposure time: 96 h Test Type: semi-static test Analytical monitoring: yes Method: OECD Test Guideline 203 GLP: yes
Toxicity to daphnia and other aquatic	: EC50 (Daphnia magna (Water flea)): > 1,000 mg/l End point: Immobilization

invertebrates	Exposure time: 48 h Test Type: semi-static test Analytical monitoring: yes Method: OECD Test Guideline 202 GLP: yes NOEC (<i>Daphnia magna</i> (Water flea)): > 1,000 mg/l End point: Immobilization Exposure time: 48 h Test Type: semi-static test Analytical monitoring: yes Method: OECD Test Guideline 202 GLP: yes
Toxicity to algae/aquatic plants	: ErC50 (<i>Pseudokirchneriella subcapitata</i> (green algae)): > 1,000 mg/l Exposure time: 72 h Test Type: static test Analytical monitoring: yes Method: OECD Test Guideline 201 GLP: yes NOEC (<i>Pseudokirchneriella subcapitata</i> (green algae)): >= 1,000 mg/l Exposure time: 72 h Test Type: static test Analytical monitoring: yes Method: OECD Test Guideline 201 GLP: yes
Toxicity to fish (Chronic toxicity)	: NOEC (<i>Pimephales promelas</i> (fathead minnow)): 0.8 mg/l Exposure time: 32 d Test Type: flow-through test Analytical monitoring: yes Remarks: (ECHA)
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: LC50 (<i>Daphnia magna</i> (Water flea)): > 100 mg/l End point: mortality Exposure time: 21 d Test Type: semi-static test Analytical monitoring: yes Method: OECD Test Guideline 211 GLP: yes
Toxicity to microorganisms	: EC50 (activated sludge): > 1,000 mg/l Exposure time: 3 h Test Type: static test Method: OECD Test Guideline 209 GLP: yes

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Cyclohexane:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 4.53 mg/l
Exposure time: 96 h
Test Type: flow-through test
Analytical monitoring: yes
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.9 mg/l
End point: Immobilization
Exposure time: 48 h
Test Type: static test
Analytical monitoring: yes
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 4.425 mg/l
Exposure time: 72 h
Analytical monitoring: yes
Method: OECD Test Guideline 201
GLP: yes

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

Toxicity to microorganisms : IC50 (Bacteria): 29 mg/l
Exposure time: 15 h
Remarks: (ECHA)

Ecotoxicology Assessment

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Persistence and degradability

Components:

benzene:

Biodegradability : aerobic
Inoculum: activated sludge, non-adapted
Concentration: 17 mg/l
Result: Readily biodegradable.
Biodegradation: 96 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

GLP: yes

Cyclohexane:

Biodegradability : aerobic
Inoculum: activated sludge, non-adapted
Concentration: 34 mg/l
Result: Readily biodegradable.
Biodegradation: 77 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
GLP: yes

Bioaccumulative potential

Components:

benzene:

Bioaccumulation : Species: Leuciscus idus (Golden orfe)
Bioconcentration factor (BCF): 10
Exposure time: 3 d
Concentration: 0.05 mg/l

Partition coefficient: n-octanol/water : log Pow: 2.13 (77 °F / 25 °C)
pH: 7
Remarks: Bioaccumulation is not expected.
(ECHA)

Cyclohexane:

Partition coefficient: n-octanol/water : log Pow: 3.44 (77 °F / 25 °C)
pH: 7
Remarks: Bioaccumulation is not expected.

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Components:

benzene:

Additional ecological : Endangers drinking-water supplies if allowed to enter

information

soil or water.

Discharge into the environment must be avoided.

Cyclohexane:

Results of PBT and vPvB assessment : Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII.

Additional ecological information : Biological effects:

Endangers drinking-water supplies if allowed to enter soil and/or waters in large quantities.

Change in the flavour characteristics of fish protein.

Discharge into the environment must be avoided.

Endocrine disrupting properties

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 3399
Proper shipping name : Organometallic substance, liquid, water-reactive, flammable (Ethyllithium, benzene, Cyclohexane)
Class : 4.3
Subsidiary risk : 3
Packing group : II
Labels : Division 4.3 - Substances which in contact with water emit flammable gases, Class 3 - Flammable liquids
Packing instruction (cargo aircraft) : 494
Packing instruction (passenger aircraft) : 493

Aldrich - 561452

Page 18 of 22

IMDG-Code

UN number : UN 3399
Proper shipping name : ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, FLAMMABLE
(Ethyllithium, benzene, Cyclohexane)
Class : 4.3
Subsidiary risk : 3
Packing group : II
Labels : 4.3 (3)
EmS Code : F-G, S-N
Marine pollutant : yes

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

National Regulations**49 CFR**

UN/ID/NA number : UN 3399
Proper shipping name : Organometallic substance, liquid, water-reactive, flammable
(Ethyllithium, benzene, Cyclohexane)
Class : 4.3
Subsidiary risk : 3
Packing group : II
Labels : Division 4.3 - Substances which in contact with water emit flammable gases, Class 3 - Flammable liquids
ERG Code : 138
Marine pollutant : no
Poison Inhalation Hazard : No

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
benzene	71-43-2	10	11
benzene	71-43-2	10	10 (D018)

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Fire Hazard
Reactivity Hazard
Acute Health Hazard
Chronic Health Hazard

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

benzene	71-43-2	>= 70 - < 90 %
Cyclohexane	110-82-7	>= 10 - < 20 %

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B). The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

benzene	71-43-2	>= 70 - < 90 %
---------	---------	----------------

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

benzene	71-43-2	>= 70 - < 90 %
Cyclohexane	110-82-7	>= 10 - < 20 %

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

benzene	71-43-2	>= 70 - < 90 %
Cyclohexane	110-82-7	>= 10 - < 20 %

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

benzene	71-43-2	>= 70 - < 90 %
Cyclohexane	110-82-7	>= 10 - < 20 %

This product contains the following toxic pollutants listed under the U.S. Clean Water Act Section 307

benzene	71-43-2	>= 70 - < 90 %
---------	---------	----------------

This product contains the following priority pollutants related to the U.S. Clean Water Act:

benzene	71-43-2	>= 70 - < 90 %
---------	---------	----------------

US State Regulations

Massachusetts Right To Know

benzene	71-43-2
Cyclohexane	110-82-7

Pennsylvania Right To Know

benzene	71-43-2
Cyclohexane	110-82-7

Maine Chemicals of High Concern

benzene	71-43-2
---------	---------

Vermont Chemicals of High Concern

benzene

71-43-2

Washington Chemicals of High Concern

benzene

71-43-2

California Prop. 65

WARNING: This product can expose you to chemicals including benzene, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. **The components of this product are reported in the following inventories:**

US TSCA : Product contains substance(s) not listed on TSCA inventory.

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	: USA. Occupational Exposure Limits (OSHA) - Table Z-2
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	: 8-hour time weighted average
OSHA Z-2 / TWA	: 8-hour time weighted average
OSHA Z-2 / CEIL	: Acceptable ceiling concentration
OSHA Z-2 / Peak	: Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide;

GHS - Globally Harmonised System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2025 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

Revision Date : 07/15/2026

US / EN