

SAFETY DATA SHEET

according to the OSHA
Hazard Communication Standard

Version 7.15
Revision Date 05/18/2026
Print Date 05/19/2026

SECTION 1. IDENTIFICATION

1.1 Product identifiers

Product name : n-Butyl-sec-butylmagnesium solution

Product Number : 752142

Brand : Aldrich

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

Uses advised against : The product is being supplied under the TSCA R&D Exemption (40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by MilliporeSigma.

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 SPRUCE ST
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765

Fax : +1 800 325-5052

1.4 Emergency telephone number

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-
527-3887 CHEMTREC (International) 24
Hours/day; 7 Days/week

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Hazards for the product as supplied

Flammable liquids : Category 2

Chemicals which, in contact with water, emit flammable gases	: Category 1
Skin corrosion	: Category 1B
Serious eye damage	: Category 1
Germ cell mutagenicity	: Category 1B
Carcinogenicity	: Category 1B
Reproductive toxicity	: Category 2
Specific target organ toxicity - single exposure	: Category 3 (Central nervous system)
Specific target organ toxicity - repeated exposure (Inhalation)	: Category 1 (Nervous system)
Aspiration hazard	: Category 1
Short-term (acute) aquatic hazard	: Category 2
Long-term (chronic) aquatic hazard	: Category 2

Other hazards

Reacts violently with water.

GHS label elements

Hazard pictograms : 

Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
H260 In contact with water releases flammable gases which may ignite spontaneously.
H304 May be fatal if swallowed and enters airways.
H314 Causes severe skin burns and eye damage.
H336 May cause drowsiness or dizziness.
H340 May cause genetic defects.
H350 May cause cancer.
H361 Suspected of damaging fertility or the unborn child.
H372 Causes damage to organs (Nervous system)

through prolonged or repeated exposure if inhaled.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements :

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P223 Do not allow contact with water.
P231 + P232 Handle under inert gas. Protect from moisture.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P335 + P334 Brush off loose particles from skin. Immerse in cool water/ wrap in wet bandages.
P363 Wash contaminated clothing before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391 Collect spillage.

Storage:

P402 + P404 Store in a dry place. Store in a closed container.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

CAS-No. : Not Assigned

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
n-Hexane	110-54-3*	$\geq 50 - < 70$	-
Naphtha (petroleum), hydrotreated light	64742-49-0*	$\geq 50 - < 70$	-
Butyl(1-methylpropyl)magnesium	39881-32-8*	$\geq 20 - < 30$	-
Cyclohexane	110-82-7*	$\geq 10 - < 20$	-

* Indicates that the identifier is a CAS No.

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : First aiders need to protect themselves.
Show this safety data sheet to the doctor in attendance.

If inhaled : After inhalation: fresh air. Call in physician.

In case of skin contact : In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.
Call a physician immediately.

In case of eye contact : After eye contact: rinse out with plenty of water.
Immediately call in ophthalmologist.
Remove contact lenses.

If swallowed	: After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation). Pulmonary failure possible after aspiration of vomit. Call a physician immediately. Do not attempt to neutralise.
Most important symptoms and effects, both acute and delayed	: The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
Protection of first-aiders	: For personal protection see section 8.
Notes to physician	: Do not induce vomiting: contains petroleum distillates and/or aromatic solvents.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Carbon dioxide (CO ₂) Dry powder
------------------------------	---

Unsuitable extinguishing media	: Water Foam
--------------------------------	-----------------

Specific hazards during fire fighting	: Combustible.
---------------------------------------	----------------

Pay attention to flashback.

May not get in touch with: Water

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

Hazardous combustion products	: Carbon oxides
-------------------------------	-----------------

Specific extinguishing methods	: No data available
--------------------------------	---------------------

Further information	: Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.
Special protective equipment for fire-fighters	: Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Advice for non-emergency personnel: Do not breathe vapours, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. Advice for emergency responders: For personal protection see section 8.
Environmental precautions	: Do not let product enter drains. Risk of explosion.
Methods and materials for containment and cleaning up	: Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

SECTION 7. HANDLING AND STORAGE

For precautions see section 2.2.

Advice on protection against fire and explosion	: Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.
Advice on safe handling	: Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols. Keep workplace dry. Do not allow product to come into contact with water.
Further information on storage conditions	: Tightly closed. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to

qualified or authorised persons.

- Materials to avoid : Never allow product to get in contact with water during storage.
- Storage class : 4.3, Hazardous materials, which set free flammable gases upon contact with water
- Recommended storage temperature : Recommended storage temperature see product label.
- Further information on storage stability : Handle and store under inert gas.
Product is sensitive to light and moisture.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
n-Hexane	110-54-3	TWA	50 ppm	ACGIH
		TWA	50 ppm 180 mg/m ³	NIOSH REL
		TWA	500 ppm 1,800 mg/m ³	OSHA Z-1
Naphtha (petroleum), hydrotreated light	64742-49-0	TWA	500 ppm 2,000 mg/m ³	OSHA Z-1
		TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA (Mist)	5 mg/m ³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
Cyclohexane	110-82-7	TWA	100 ppm	ACGIH
		TWA	300 ppm 1,050 mg/m ³	NIOSH REL
		TWA	300 ppm 1,050 mg/m ³	OSHA Z-1

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
n-Hexane	110-54-3	2,5-Hexanedione	Urine	End of shift	0.5 mg/l	ACGIH BEI
Cyclohexane	110-82-7	1,2-Cyclohexanediol	Urine	End of shift at end of workweek	50 mg/g creatinine	ACGIH BEI

Engineering measures : No data available

Personal protective equipment

Respiratory protection : required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Recommended Filter type: : Filter type ABEK

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Hand protection

Remarks : required

Eye protection : Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).
Tightly fitting safety goggles

Skin and body protection : Flame retardant antistatic protective clothing.

Hygiene measures : Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : light yellow

Odor : solvent-like

Odor Threshold : No data available

pH	: No data available
Melting point	: No data available
Boiling point/boiling range	: No data available
Flash point	: < -22 °F / < -30 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Flammability (liquids)	: No data available
Burning rate	: No data available
Self-ignition	: The substance or mixture is not classified as pyrophoric.
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapor pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available
Density	: 0.695 g/cm ³ (77 °F / 25 °C)
Water solubility	: No data available
Partition coefficient: n- octanol/water	: No data available
Autoignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Flow time	: No data available
Explosive properties	: Not classified as explosive.

Oxidizing properties : none
Molecular weight : 138.53 g/mol
Particle characteristics
Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Vapours may form explosive mixture with air.
Chemical stability : sensitive to moisture
Possibility of hazardous reactions : No data available
Conditions to avoid : Warming.
Moisture.
Incompatible materials : Water
Acids
Oxidizing agents
Hazardous decomposition products : In the event of fire: see section 5

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Mixture

Acute toxicity

Oral: No data available

Symptoms: If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the oesophagus and the stomach.

Inhalation: No data available

Dermal: No data available

Skin corrosion/irritation

Remarks: Mixture causes burns.

Serious eye damage/eye irritation

Remarks: Mixture causes serious eye damage.

Risk of blindness!

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

Possible mutagen

Aldrich - 752142

Page 10 of 22

Carcinogenicity

Possible carcinogen.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

Suspected of damaging the unborn child.

Suspected of damaging fertility.

Specific target organ toxicity - single exposure

Mixture may cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Mixture causes damage to organs through prolonged or repeated exposure.

- Nervous system

Aspiration hazard

Aspiration hazard, Aspiration may cause pulmonary oedema and pneumonitis.

11.2 Additional Information

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Other dangerous properties can not be excluded.

This substance should be handled with particular care.

Handle in accordance with good industrial hygiene and safety practice.

Components

n-Hexane

Acute toxicity

LD50 Oral - Rat - male and female - 16,000 mg/kg

(OECD Test Guideline 401)

LC50 Inhalation - Rat - 4 h - 172 mg/l - vapour

Remarks: (RTECS)

LD50 Dermal - Rabbit - male - > 2,000 mg/kg

(OECD Test Guideline 402)

Skin corrosion/irritation

Skin - Rabbit

Result: Skin irritation - 24 h

(OECD Test Guideline 404)

Remarks: (Regulation (EC) No 1272/2008, Annex VI)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation - 72 h

(OECD Test Guideline 405)

Respiratory or skin sensitization

Local lymph node assay (LLNA) - Mouse

Result: negative

(OECD Test Guideline 429)

Germ cell mutagenicity

Test Type: Ames test

Test system: Salmonella typhimurium

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: Mouse lymphoma test

Result: negative

Method: OECD Test Guideline 478

Species: Mouse - male

Result: negative

Method: OECD Test Guideline 475

Species: Rat - male and female - Bone marrow

Result: negative

Carcinogenicity

No data available

Reproductive toxicity

Suspected of damaging fertility.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness. - Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Specific target organ toxicity - repeated exposure

Inhalation - Causes damage to organs through prolonged or repeated exposure.

- Nervous system

Aspiration hazard

Aspiration may cause pulmonary oedema and pneumonitis.

Naphtha (petroleum), hydrotreated light**Acute toxicity**

LD50 Oral - Rat - male and female - > 5,000 mg/kg

(OECD Test Guideline 401)

Remarks: (in analogy to similar compounds)

LC50 Inhalation - Rat - male and female - 4 h - > 5,610 mg/m³ - vapour

(OECD Test Guideline 403)

Remarks: (in analogy to similar products)

LD50 Dermal - Rabbit - male and female - > 2,000 mg/kg

(OECD Test Guideline 402)

Remarks: (in analogy to similar products)

Skin corrosion/irritation

Skin - Rabbit

Result: Skin irritation - 4 h

(OECD Test Guideline 404)

Remarks: (in analogy to similar products)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation

(OECD Test Guideline 405)

Remarks: (in analogy to similar products)

Respiratory or skin sensitization

Buehler Test - Guinea pig

Result: negative

(OECD Test Guideline 406)

Remarks: (in analogy to similar products)

Germ cell mutagenicity

May cause genetic defects.

Test Type: sister chromatid exchange assay

Test system: Chinese hamster ovary cells

Result: negative

Remarks: (ECHA)

(in analogy to similar products)

Test Type: Ames test

Test system: *S. typhimurium*

Result: negative

Remarks: (in analogy to similar products)

Method: US-EPA

Species: Rat - male and female

Result: negative

Remarks: (in analogy to similar products)

Carcinogenicity

Presumed to have carcinogenic potential for humans

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

Aspiration may cause pulmonary oedema and pneumonitis.

Butyl(1-methylpropyl)magnesium**Acute toxicity**

Oral: No data available

Inhalation: No data available

Dermal: No data available

Skin corrosion/irritation

Remarks: No data available

Serious eye damage/eye irritation

Remarks: No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Cyclohexane**Acute toxicity**

LD50 Oral - Rat - male and female - > 5,000 mg/kg
(OECD Test Guideline 401)

Symptoms: gastric pain, Stomach/intestinal disorders

LC50 Inhalation - Rat - male and female - 4 h - > 32,800 mg/l - vapour
(OECD Test Guideline 403)

Symptoms: Possible damages:, Irritation symptoms in the respiratory tract.,
Inhalation may lead to the formation of oedemas in the respiratory tract.

LD50 Dermal - Rabbit - male and female - > 2,000 mg/kg
(OECD Test Guideline 402)

Skin corrosion/irritation

Remarks: Causes skin irritation.

Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Serious eye damage/eye irritation

Remarks: No data available

Respiratory or skin sensitization

Buehler Test - Guinea pig

Result: negative
(Regulation (EC) No. 440/2008, Annex, B.6)

Germ cell mutagenicity

Test Type: Ames test
Test system: Salmonella typhimurium
Result: negative
Test Type: In vitro mammalian cell gene mutation test
Test system: Mouse lymphoma test
Result: negative
Method: OECD Test Guideline 475
Species: Rat - male and female - Bone marrow
Result: negative

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.
Acute oral toxicity - gastric pain, Stomach/intestinal disorders
Acute inhalation toxicity - Possible damages:, Irritation symptoms in the respiratory tract., Inhalation may lead to the formation of oedemas in the respiratory tract.

Specific target organ toxicity - repeated exposure

Aspiration hazard

May be fatal if swallowed and enters airways. Aspiration hazard, Aspiration may cause pulmonary oedema and pneumonitis.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

n-Hexane:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2.5 mg/l
Exposure time: 96 h
Remarks: (ECOTOX Database)

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 2.1 mg/l
Exposure time: 48 h
Remarks: (Lit.)

Naphtha (petroleum), hydrotreated light:

Toxicity to fish : LC50 (other fish): 1 - 10 mg/l
Exposure time: 96.0 h

Toxicity to daphnia and : EC50 (Daphnia magna (Water flea)): 1.26 - 12.60

other aquatic
invertebrates

mg/l
Exposure time: 48 h
Remarks: (External MSDS)

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 4.53 mg/l
Exposure time: 96 h
Test Type: flow-through test
Analytical monitoring: yes
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 0.9 mg/l End point: Immobilization Exposure time: 48 h Test Type: static test Analytical monitoring: yes Method: OECD Test Guideline 202
---	--

Toxicity to algae/aquatic plants : ErC50 (*Pseudokirchneriella subcapitata* (green algae)): > 4.425 mg/l
Exposure time: 72 h
Analytical monitoring: yes
Method: OECD Test Guideline 201
GLP: yes

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

Toxicity to microorganisms : IC50 (Bacteria): 29 mg/l
Exposure time: 15 h
Remarks: (ECHA)

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Components:

Biodegradability : aerobic
Inoculum: activated sludge
Concentration: 100 mg/l
Result: Readily biodegradable.
Biodegradation: 98 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Page 16 of 22

GLP: yes
Remarks: (in analogy to similar products)

Naphtha (petroleum), hydrotreated light:

Biodegradability : Biotic/Aerobic
Result: Not readily biodegradable.
Remarks: (External MSDS)

Cyclohexane:

Biodegradability : aerobic
Inoculum: activated sludge, non-adapted
Concentration: 34 mg/l
Result: Readily biodegradable.
Biodegradation: 77 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
GLP: yes

Bioaccumulative potential

Components:

n-Hexane:

Partition coefficient: n-octanol/water : log Pow: ca. 4 (68 °F / 20 °C)
Method: (experimental)
Remarks: (Lit.)
Potential bioaccumulation

Cyclohexane:

Partition coefficient: n-octanol/water : log Pow: 3.44 (77 °F / 25 °C)
pH: 7
Remarks: Bioaccumulation is not expected.

Mobility in soil

Components:

n-Hexane:

Stability in soil : Remarks: No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Components:

n-Hexane:

Results of PBT and vPvB assessment : Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII.

Cyclohexane:

Results of PBT and vPvB assessment : Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII.

Additional ecological information : Biological effects:

Endangers drinking-water supplies if allowed to enter soil and/or waters in large quantities.

Change in the flavour characteristics of fish protein.

Discharge into the environment must be avoided.

Endocrine disrupting properties

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 3399
Proper shipping name : Organometallic substance, liquid, water-reactive, flammable (Butyl(1-methylpropyl)magnesium, n-Hexane)
Class : 4.3
Subsidiary risk : 3
Packing group : I
Labels : Division 4.3 - Substances which in contact with water emit flammable gases, Class 3 - Flammable liquids
Packing instruction (cargo) : 494

Aldrich - 752142

Page 18 of 22

aircraft)
Packing instruction : Not permitted for transport
(passenger aircraft)

IMDG-Code

UN number : UN 3399
Proper shipping name : ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-
REACTIVE, FLAMMABLE
(Butyl(1-methylpropyl)magnesium, n-Hexane)
Class : 4.3
Subsidiary risk : 3
Packing group : I
Labels : 4.3 (3)
EmS Code : F-G, S-N
Marine pollutant : yes

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

National Regulations**49 CFR**

UN/ID/NA number : UN 3399
Proper shipping name : Organometallic substance, liquid, water-reactive,
flammable
(Butyl(1-methylpropyl)magnesium, n-Hexane)
Class : 4.3
Subsidiary risk : 3
Packing group : I
Labels : Division 4.3 - Substances which in contact with water
emit flammable gases, Class 3 - Flammable liquids
ERG Code : 138
Marine pollutant : no
Poison Inhalation Hazard : No

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**CERCLA Reportable Quantity**

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Fire Hazard
 Reactivity Hazard
 Acute Health Hazard
 Chronic Health Hazard

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

n-Hexane	110-54-3	>= 50 - < 70 %
Cyclohexane	110-82-7	>= 10 - < 20 %

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B). The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

n-Hexane	110-54-3	>= 50 - < 70 %
----------	----------	----------------

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

Cyclohexane	110-82-7	>= 10 - < 20 %
-------------	----------	----------------

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

Cyclohexane	110-82-7	>= 10 - < 20 %
-------------	----------	----------------

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

Cyclohexane	110-82-7	>= 10 - < 20 %
-------------	----------	----------------

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

n-Hexane	110-54-3
Naphtha (petroleum), hydrotreated light	64742-49-0
Cyclohexane	110-82-7

Pennsylvania Right To Know

n-Hexane	110-54-3
Naphtha (petroleum), hydrotreated light	64742-49-0
Cyclohexane	110-82-7

Maine Chemicals of High Concern

Product does not contain any listed chemicals

Vermont Chemicals of High Concern

Product does not contain any listed chemicals

Washington Chemicals of High Concern

Product does not contain any listed chemicals

California Prop. 65

WARNING: This product can expose you to chemicals including n-Hexane, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. **The components of this product are reported in the following inventories:**

US TSCA : All substances listed as active on the TSCA inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	: 8-hour, time-weighted average
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	: 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not

Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2025 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

Revision Date : 05/18/2026

US / EN