

SAFETY DATA SHEET

according to the OSHA
Hazard Communication Standard

Version 8.15
Revision Date 08/03/2026
Print Date 08/04/2026

SECTION 1. IDENTIFICATION

1.1 Product identifiers

Product name : Benzene GR ACS

Product Number : BX0220
Brand : Millipore
Index-No. : 601-020-00-8
CAS-No. : 71-43-2

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Reagent for analysis
Restrictions on use : Not Available

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
SPRUCE ST 3050
63103 St. Louis

Telephone : (314) 771-5765
Telefax: (800) 325-5052

1.4 Emergency telephone number

Emergency Phone # : 800 424 9300 (CHEMTREC) 24/7
+1 703 527 3887 (CHEMTREC) 24/7

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Hazards for the product as supplied

Flammable liquids : Category 2

Skin irritation : Category 2

Eye irritation	: Category 2A
Germ cell mutagenicity	: Category 1B
Carcinogenicity	: Category 1A
Specific target organ toxicity - repeated exposure	: Category 1 (Blood)
Aspiration hazard	: Category 1
Long-term (chronic) aquatic hazard	: Category 3

Other hazards

None known.

GHS label elements

Hazard pictograms : 

Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H340 May cause genetic defects.
H350 May cause cancer.
H372 Causes damage to organs (Blood) through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.
P273 Avoid release to the environment.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

CAS-No. : 71-43-2

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
benzene	71-43-2*	>= 80 - <= 100	TSC

* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

Millipore - BX0220

Page 3 of 18

The life science business of Merck KGaA, Darmstadt, Germany operates as MilliporeSigma in the US and Canada

MILLIPORE
SIGMA

General advice	: Show this safety data sheet to the doctor in attendance.
If inhaled	: After inhalation: fresh air. Call in physician.
In case of skin contact	: In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.
In case of eye contact	: After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.
If swallowed	: After swallowing: caution if victim vomits. Risk of aspiration! Keep airways free. Pulmonary failure possible after aspiration of vomit. Call a physician immediately.
Most important symptoms and effects, both acute and delayed	: The most important known symptoms and effects are described in the labelling (see section 2 GHS label elements) and/or in section 11
Protection of first-aiders	: For personal protection see section 8.
Notes to physician	: No data available

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Carbon dioxide (CO ₂) Foam Dry powder
Unsuitable extinguishing media	: For this substance/mixture no limitations of extinguishing agents are given.
Specific hazards during fire fighting	: Combustible.

Pay attention to flashback.

Vapours are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

Hazardous combustion products	: Carbon oxides
Specific extinguishing methods	: No data available
Further information	: Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.
Special protective equipment for fire-fighters	: Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Advice for non-emergency personnel: Do not breathe vapours, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. Advice for emergency responders: Wear appropriate personal protective equipment, as indicated in Section 8.
Environmental precautions	: Do not let product enter drains. Risk of explosion.
Methods and materials for containment and cleaning up	: Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

SECTION 7. HANDLING AND STORAGE

For precautions see section 2 GHS label elements

- Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition.
Take precautionary measures against static discharge.
- Advice on safe handling : Work under hood. Do not inhale substance/mixture.
Avoid generation of vapours/aerosols.
- Further information on storage conditions : Keep container tightly closed in a dry and well-ventilated place.
Keep away from heat and sources of ignition.
Keep locked up or in an area accessible only to qualified or authorised persons.
- Storage class : 3, Flammable liquids
- Recommended storage temperature : Recommended storage temperature see product label.
- Further information on storage stability : Recommended storage temperature see product label.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
benzene	71-43-2	TWA	0.5 ppm	ACGIH
		STEL	2.5 ppm	ACGIH
		TWA	10 ppm	OSHA Z-2
		CEIL	25 ppm	OSHA Z-2
		Peak	50 ppm	OSHA Z-2
		TWA	0.1 ppm	NIOSH REL
		ST	1 ppm	NIOSH REL

Engineering measures : No data available

Personal protective equipment

Respiratory protection : required when vapours/aerosols are generated.
Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Recommended Filter : Filter A-(P3)
Millipore - BX0220

Page 6 of 18

type:

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Hand protection

Material : Viton®
Break through time : 480 min
Glove thickness : 0.7 mm
Protective index : Full contact
Manufacturer : Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Material : Nitrile rubber
Break through time : 10 min
Glove thickness : 0.4 mm
Protective index : Splash contact
Manufacturer : Camatril® (KCL 730 / Aldrich Z677442, Size M)

Remarks : This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Eye protection : Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).
Safety glasses

Skin and body protection : Flame retardant antistatic protective clothing.

Hygiene measures : Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : colourless

Odour : No data available

Odour Threshold	: No data available
pH	: No data available
Melting point/ range	: 41.9 °F / 5.5 °C
Boiling point/boiling range	: 176.2 °F / 80.1 °C
Flash point	: 12 °F / -11 °C (1,013.5 hPa) Method: DIN 51755 Part 1
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Flammability (liquids)	: No data available
Burning rate	: No data available
Self-ignition	: 928 °F / 498 °C 1,013.5 hPa
Upper explosion limit / Upper flammability limit	: Upper explosion limit 8.0 %(V)
Lower explosion limit / Lower flammability limit	: Lower explosion limit 1.2 %(V)
Vapour pressure	: 100 hPa (68 °F / 20 °C)
Relative vapour density	: No data available
Relative density	: No data available
Density	: 0.88 g/cm ³ (68 °F / 20 °C)
Solubility(ies)	
Water solubility	: ca. 1.88 g/l soluble (74.3 °F / 23.5 °C) pH: 7
Partition coefficient: n- octanol/water	: log Pow: 2.13 (77 °F / 25 °C) pH: 7 Bioaccumulation is not expected. (ECHA)
Autoignition temperature	: 928 °F / 498 °C (1,013.5 hPa)
Decomposition temperature	: No data available

Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: 0.604 mm ² /s (77 °F / 25 °C)
Flow time	: No data available
Explosive properties	: Not classified as explosive.
Oxidizing properties	: none
Molecular weight	: 78.11 g/mol
Particle characteristics	
Particle size	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Vapours may form explosive mixture with air.
Chemical stability	: The product is chemically stable under standard ambient conditions (room temperature) .
Possibility of hazardous reactions	: Exothermic reaction with: halogens Halogenated hydrocarbon in the presence of: Light metals Risk of explosion with: halogen-halogen compounds Nitric acid Boranes Ozone peroxi compounds perchlorates permanganic acid perchloryl fluoride Strong oxidizing agents Chlorine fluorides uranium hexafluoride Oxygen liquid Risk of ignition or formation of inflammable gases or vapours with: chromium(VI) oxide Fluorine nitryl compounds Oxygen oxyhalogenic compounds

Violent reactions possible with:
mineral acids
sulfur

Conditions to avoid : Warming.

Incompatible materials : No data available

Hazardous decomposition products : For Hazardous combustion products in the event of fire: see section 5

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male - > 2,000 mg/kg
(OECD Test Guideline 401)

Symptoms: Nausea

LD50 Oral - Rat - male and female - 3,002 mg/kg
(OECD Test Guideline 401)

Symptoms: Risk of aspiration upon vomiting., Aspiration may cause pulmonary oedema and pneumonitis.

Inhalation: No data available

Symptoms: mucosal irritations

LD50 Dermal - Rabbit - 13,630 mg/kg

Remarks: (IUCLID)

No data available

Skin corrosion/irritation

Skin - Rabbit

Result: irritating

(OECD Test Guideline 404)

Remarks: (ECHA)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Irritating to eyes.

(OECD Test Guideline 405)

Remarks: (IUCLID)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Respiratory or skin sensitization

Maximisation Test - Guinea pig

Result: negative

(OECD Test Guideline 406)

Germ cell mutagenicity

May cause genetic defects.

Test Type: Ames test

Test system: Escherichia coli/Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Millipore - BX0220

Page 10 of 18

Test Type: In vitro mammalian cell gene mutation test
Test system: mouse lymphoma cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative
Test Type: Chromosome aberration test in vitro
Test system: Chinese hamster lung cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: negative

Test Type: Mutagenicity (mammal cell test): micronucleus.
Species: Mouse
Cell type: Bone marrow
Application Route: inhalation (vapour)
Method: OECD Test Guideline 474
Result: positive

Carcinogenicity

May cause cancer. Positive evidence from human epidemiological studies.

IARC: 1 - Group 1: Carcinogenic to humans (benzene)

NTP: Known - Known to be human carcinogen (benzene)

OSHA: OSHA specifically regulated carcinogen (benzene)

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

- Blood

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Aspiration hazard

Aspiration may cause pulmonary oedema and pneumonitis.

11.2 Additional Information

Repeated dose toxicity - Rat - male and female - Oral - 13 Weeks - No observed adverse effect level - 600 mg/kg

Nausea, Dizziness, Headache, narcosis, Inhalation of high concentrations of benzene may have an initial stimulatory effect on the central nervous system characterized by exhilaration, nervous excitation and/or giddiness, depression, drowsiness, or fatigue. The victim may experience tightness in the chest, breathlessness, and loss of consciousness. Tremors, convulsions, and death due to respiratory paralysis or circulatory collapse can occur in a few minutes to several hours following severe exposures. Aspiration of small amounts of liquid immediately causes pulmonary edema and hemorrhage of pulmonary tissue. Direct skin contact may cause erythema. Repeated or prolonged skin contact may result in drying, scaling dermatitis, or development of secondary skin infections. The chief target organ is the hematopoietic system. Bleeding from the nose, gums, or mucous membranes and the development of purpuric spots, pancytopenia, leukopenia,

thrombocytopenia, aplastic anemia, and leukemia may occur as the condition progresses. The bone marrow may appear normal, aplastic or hyperplastic, and may not correlate with peripheral blood-forming tissues. The onset of effects of prolonged benzene exposure may be delayed for many months or years after the actual exposure has ceased., Blood disorders

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

After absorption of large quantities:

narcosis
respiratory arrest
Convulsions

Possible damages:

Damage to:

Liver
Kidney
Central nervous system

Handle in accordance with good industrial hygiene and safety practice.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

benzene:

Toxicity to fish : LC50 (*Oryzias latipes* (Orange-red killifish)): > 100 mg/l
End point: mortality
Exposure time: 96 h
Test Type: semi-static test
Analytical monitoring: yes
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): > 1,000 mg/l
End point: Immobilization
Exposure time: 48 h
Test Type: semi-static test
Analytical monitoring: yes
Method: OECD Test Guideline 202
GLP: yes

NOEC (*Daphnia magna* (Water flea)): > 1,000 mg/l
End point: Immobilization

Exposure time: 48 h
Test Type: semi-static test
Analytical monitoring: yes
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic plants : ErC50 (*Pseudokirchneriella subcapitata* (green algae)): > 1,000 mg/l

Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Method: OECD Test Guideline 201
GLP: yes

NOEC (*Pseudokirchneriella subcapitata* (green algae)):
>= 1,000 mg/l

Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Method: OECD Test Guideline 201
GLP: yes

Toxicity to fish (Chronic toxicity) : NOEC (*Pimephales promelas* (fathead minnow)): 0.8 mg/l

Exposure time: 32 d
Test Type: flow-through test
Analytical monitoring: yes
Remarks: (ECHA)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : LC50 (*Daphnia magna* (Water flea)): > 100 mg/l
End point: mortality

Exposure time: 21 d
Test Type: semi-static test
Analytical monitoring: yes
Method: OECD Test Guideline 211
GLP: yes

Toxicity to microorganisms : EC50 (activated sludge): > 1,000 mg/l
Exposure time: 3 h

Test Type: static test
Method: OECD Test Guideline 209
GLP: yes

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Persistence and degradability

Components:

benzene:

Biodegradability : aerobic
Inoculum: activated sludge, non-adapted
Concentration: 17 mg/l
Result: Readily biodegradable.
Biodegradation: 96 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
GLP: yes

Bioaccumulative potential

Components:

benzene:

Bioaccumulation : Species: Leuciscus idus (Golden orfe)
Bioconcentration factor (BCF): 10
Exposure time: 3 d
Concentration: 0.05 mg/l

Partition coefficient: n-octanol/water : log Pow: 2.13 (77 °F / 25 °C)
pH: 7
Remarks: Bioaccumulation is not expected.
(ECHA)

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Components:

benzene:

Additional ecological information : Endangers drinking-water supplies if allowed to enter soil or water.

Discharge into the environment must be avoided.

Endocrine disrupting properties

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1114
Proper shipping name : Benzene
Class : 3
Packing group : II
Labels : Class 3 - Flammable liquids
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353

IMDG-Code

UN number : UN 1114
Proper shipping name : BENZENE

Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-D
Marine pollutant : no

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number : UN 1114
Proper shipping name : Benzene

Class : 3

Packing group : II
Labels : Class 3 - Flammable liquids
ERG Code : 130
Marine pollutant : no
Poison Inhalation Hazard : No

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
benzene	71-43-2	10	10
benzene	71-43-2	10	10 (D018)

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

benzene 71-43-2 >= 90 - <= 100 %

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B). The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

benzene 71-43-2 >= 90 - <= 100 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489):

benzene 71-43-2 >= 90 - <= 100 %

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

benzene 71-43-2 >= 90 - <= 100 %

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

benzene 71-43-2 >= 90 - <= 100 %

This product contains the following toxic pollutants listed under the U.S. Clean Water Act Section 307

benzene 71-43-2 >= 90 - <= 100 %

This product contains the following priority pollutants related to the U.S. Clean Water Act:

benzene 71-43-2 >= 90 - <= 100 %

US State Regulations

Massachusetts Right To Know

benzene	71-43-2
Pennsylvania Right To Know	
benzene	71-43-2
Maine Chemicals of High Concern	
benzene	71-43-2
Vermont Chemicals of High Concern	
benzene	71-43-2
Washington Chemicals of High Concern	
benzene	71-43-2

California Prop. 65

WARNING: This product can expose you to chemicals including benzene, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. **The components of this product are reported in the following inventories:**

US TSCA : All substances listed as active on the TSCA inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA Z-2	: USA. Occupational Exposure Limits (OSHA) - Table Z-2
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-2 / TWA	: 8-hour time weighted average
OSHA Z-2 / CEIL	: Acceptable ceiling concentration
OSHA Z-2 / Peak	: Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response;

EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2025 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

Revision Date : 08/03/2026

US / EN