

## SAFETY DATA SHEET

Version 8.15 Revision Date 08/07/2024 Print Date 08/08/2024

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

# 1.1 Product identifiers

Product name : Methanol For HPLC Gradient Analysis,

<br/>Spectrophotometry and <br/>Gas

Chromatography OmniSolv®

Product Number : MX0488
Catalogue No. : FX0168
Brand : Millipore
Index-No. : 603-001-00-X
CAS-No. : 67-56-1

# 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Reagent for analysis

Uses advised against : The product is being supplied under the TSCA R&D Exemption

(40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by

MilliporeSigma.

### 1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.

3050 SPRUCE ST ST. LOUIS MO 63103 UNITED STATES

Telephone : +1 314 771-5765 Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-

527-3887 CHEMTREC (International) 24

Hours/day; 7 Days/week

#### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225

Millipore - MX0488

Page 1 of 14



Acute toxicity, Oral (Category 3), H301 Acute toxicity, Inhalation (Category 3), H331 Acute toxicity, Dermal (Category 3), H311

Specific target organ toxicity - single exposure (Category 1), Eyes, Central nervous system, H370

For the full text of the H-Statements mentioned in this Section, see Section 16.

## 2.2 GHS Label elements, including precautionary statements

Pictogram Signal Word Danger **Hazard Statements** Highly flammable liquid and vapor. H225 Toxic if swallowed, in contact with skin or if inhaled. H301 + H311 + H331 Causes damage to organs (Eyes, Central nervous system). H370 **Precautionary Statements** Keep away from heat/ sparks/ open flames/ hot surfaces. No P210 smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe mist or vapors. P264 Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. P270 P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ eye protection/ face protection. P301 + P310 + P330 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. Rinse mouth. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF INHALED: Remove person to fresh air and keep comfortable P304 + P340 + P311 for breathing. Call a POISON CENTER/ doctor. IF exposed: Call a POISON CENTER or doctor/ physician. P307 + P311 P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P403 + P235 Store in a well-ventilated place. Keep cool.

### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

plant.

Store locked up.

Dispose of contents/ container to an approved waste disposal

Millipore - MX0488

P405

P501



### **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

Formula : CH40

Molecular weight : 32.04 g/mol

CAS-No. : 67-56-1

EC-No. : 200-659-6

Index-No. : 603-001-00-X

Component	Classification	Concentration
Methanol		
	Flam. Liq. 2; Acute Tox. 3; STOT SE 1; H225, H301, H331, H311, H370	<= 100 %
	Concentration limits: >= 10 %: STOT SE 1, H370; 3 - < 10 %: STOT SE 2, H371;	

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### **SECTION 4: First aid measures**

## 4.1 Description of first-aid measures

## **General advice**

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

#### If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

#### In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

#### In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

#### If swallowed

After swallowing: fresh air. Make victim drink ethanol (e.g. 1 drinking glass of a 40% alcoholic beverage). Call a doctor immediately (mention methanol ingestion). Only in exceptional cases, if no medical care is available within one hour, induce vomiting (only in fully conscious persons) and make victim drink ethanol again (approx. 0.3 ml of a 40% alcoholic beverage/kg body weight/hour).

### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

Millipore - MX0488

Page 3 of 14



# 4.3 Indication of any immediate medical attention and special treatment needed

No data available

## **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media

### Suitable extinguishing media

Water Foam Carbon dioxide (CO2) Dry powder

## Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

## 5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

#### 5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

#### 5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

#### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

## 6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

## 6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb $^{\circ}$ ). Dispose of properly. Clean up affected area.

## 6.4 Reference to other sections

For disposal see section 13.



### **SECTION 7: Handling and storage**

## 7.1 Precautions for safe handling

## Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

## Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

### **Hygiene measures**

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

## 7.2 Conditions for safe storage, including any incompatibilities

### **Storage conditions**

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorized persons.

Recommended storage temperature see product label.

#### Storage class

Storage class (TRGS 510): 3: Flammable liquids

## 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Ingredients with workplace control parameters

Ingredients with workplace control parameters					
Component	CAS-No.	Value	Control	Basis	
			parameters		
Methanol	67-56-1	TWA	200 ppm	USA. ACGIH Threshold Limit	
				Values (TLV)	
	Remarks	Danger of cutaneous absorption			
		STEL	250 ppm	USA. ACGIH Threshold Limit	
				Values (TLV)	
		Danger of cutaneous absorption			
		ST	250 ppm	USA. NIOSH Recommended	
			325 mg/m3	Exposure Limits	
		Potential for dermal absorption			
		TWA	200 ppm	USA. NIOSH Recommended	
			260 mg/m3	Exposure Limits	
		Potential for dermal absorption			

Millipore - MX0488 Page 5 of 14



TWA	200 ppm 260 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
PEL	200 ppm 260 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
Skin		
С	1,000 ppm	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
Skin		
STEL	250 ppm 325 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
Skin		

**Biological occupational exposure limits** 

Diological occupational exposure initia					
Component	CAS-No.	Parameters	Value	Biological specimen	Basis
Methanol	67-56-1	Methanol	15 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift (As soon as possible after exposure ceases)			

## 8.2 Exposure controls

### **Appropriate engineering controls**

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

### Personal protective equipment

## Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

#### Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.7 mm Break through time: 480 min Material tested:Butoject® (KCL 898)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please

Millipore - MX0488 Page 6 of 14



contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de).

Splash contact Material: Viton®

Minimum layer thickness: 0.7 mm Break through time: 120 min

Material tested:Vitoject® (KCL 890 / Aldrich Z677698, Size M)

#### **Body Protection**

Flame retardant antistatic protective clothing.

## **Respiratory protection**

Recommended Filter type: Filter type AX

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented. required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

## **Control of environmental exposure**

Do not let product enter drains. Risk of explosion.

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

a) Appearance Form: liquid

Color: colorless

b) Odor characteristic

c) Odor Threshold 10 ppm

d) pH No data available

e) Melting Melting point: -97.8 °C (-144.0 °F) - (ECHA)

point/freezing point

Initial boiling point 64.7 °C

and boiling range

64.7 °C 148.5 °F at 1,013 hPa - (ECHA)

g) Flash point 9.7 °C (49.5 °F) - closed cup - Regulation (EC) No. 440/2008,

Annex, A.9

h) Evaporation rate 6.3 - Diethyl ether1.9 - n-butyl acetate

i) Flammability (solid, No d

gas)

No data available

j) Upper/lower Upper explosion limit: 44 %(V) flammability or Lower explosion limit: 5.5 %(V)

explosive limits

k) Vapor pressure 169.27 hPa at 25 °C (77 °F)

I) Vapor density 1.11

m) Density 0.79 g/cm3 at 20 °C (68 °F)

Relative density 0.79 - 0.820 °C

n) Water solubility 1,000 g/l at 20 °C (68 °F) - completely miscible

o) Partition coefficient: log Pow: -0.77 at 25 °C (77 °F) - (HSDB), Bioaccumulation is

n-octanol/water not expected.

p) Autoignition 455.0 °C (851.0 °F) at 1,013 hPa - DIN 51794

temperature

q) Decomposition Distillable in an undecomposed state at normal pressure.

temperature

r) Viscosity 0.54 - 0.59 mm2/s at 20 °C (68 °F) -

s) Explosive properties No data available

t) Oxidizing properties none

## 9.2 Other safety information

Minimum ignition 0.14 mJ

energy

Conductivity  $< 1 \mu S/cm$ 

Relative vapor 1.11

density

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

Vapors may form explosive mixture with air.

### 10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature).

## 10.3 Possibility of hazardous reactions

Risk of explosion with:

Oxidizing agents

perchloric acid

perchlorates

salts of oxyhalogenic acids

chromium(VI) oxide

halogen oxides

nitrogen oxides

nonmetallic oxides

chromosulfuric acid

chlorates

hydrides

zinc diethyl

halogens

powdered magnesium



hydrogen peroxide

Nitric acid

sulfuric acid

permanganic acid

sodium hypochlorite

Exothermic reaction with:

acid halides

Acid anhydrides

Reducing agents

acids

Bromine

Chlorine

Chloroform

magnesium

tetrachloromethane

Risk of ignition or formation of inflammable gases or vapours with:

Fluorine

Oxides of phosphorus

Raney-nickel

Generates dangerous gases or fumes in contact with:

Alkaline earth metals

Alkali metals

#### 10.4 Conditions to avoid

Warming.

#### 10.5 Incompatible materials

No data available

## 10.6 Hazardous decomposition products

In the event of fire: see section 5

## **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

## **Acute toxicity**

Acute toxicity estimate Oral - 100.1 mg/kg

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Symptoms: Nausea, Vomiting

Acute toxicity estimate Inhalation - 4 h - 3.1 mg/l - vapor

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Symptoms: Irritation symptoms in the respiratory tract.

Acute toxicity estimate Dermal - 300.1 mg/kg

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)



#### Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation

Remarks: (ECHA)

Remarks: Drying-out effect resulting in rough and chapped skin.

### Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation Remarks: (ECHA)

# Respiratory or skin sensitization

Sensitisation test: - Guinea pig

Result: negative

(OECD Test Guideline 406)

### Germ cell mutagenicity

Based on available data the classification criteria are not met.

Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster lung cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Test Type: Micronucleus test

Species: Mouse

Cell type: Bone marrow

Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

Result: negative

## Carcinogenicity

Did not show carcinogenic effects in animal experiments.

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

## Reproductive toxicity

Based on available data the classification criteria are not met.

## Specific target organ toxicity - single exposure

Causes damage to organs. - Eyes, Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

## Specific target organ toxicity - repeated exposure

No data available

Millipore - MX0488

Page 10 of 14

## Aspiration hazard

No data available

#### 11.2 Additional Information

Acute effects:, Headache, Dizziness, Drowsiness, narcosis, Blindness, Impairment of vision, irritant effects, Nausea, Vomiting, agitation, spasms, inebriation, Coma Drying-out effect resulting in rough and chapped skin.

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Systemic effects:

acidosis
drop in blood pressure
agitation, spasms
inebriation
Dizziness
Drowsiness
Headache
Impairment of vision

Blindness narcosis Coma

Symptoms may be delayed.

Damage to:

Liver Kidney Cardiac

Irreversible damage of the optical nerve.

Other dangerous properties can not be excluded.

This substance should be handled with particular care.

Stomach - Irregularities - Based on Human Evidence

## **SECTION 12: Ecological information**

### 12.1 Toxicity

Toxicity to fish flow-through test LC50 - Lepomis macrochirus (Bluegill) - 15,400.0

mg/l - 96 h (US-EPA)

Toxicity to daphnia

semi-static test EC50 - Daphnia magna (Water flea) - 18,260 mg/l -

and other aquatic 96 h

invertebrates (OECD Test Guideline 202)

Millipore - MX0488 Page 11 of 14



Toxicity to algae static test ErC50 - Pseudokirchneriella subcapitata (green algae) - ca.

22,000.0 mg/l - 96 h (OECD Test Guideline 201)

Toxicity to bacteria static test IC50 - activated sludge - > 1,000 mg/l - 3 h

(OECD Test Guideline 209)

Toxicity to NOEC - Oryzias latipes (Orange-red killifish) - 7,900 mg/l - 200 h

fish(Chronic toxicity) Remarks: (External MSDS)

## 12.2 Persistence and degradability

Biodegradability Result: 99 % - Readily biodegradable.

(OECD Test Guideline 301D)

Biochemical Oxygen 600 - 1,120 mg/g Demand (BOD) Remarks: (IUCLID)

Chemical Oxygen 1,420 mg/g

Demand (COD) Remarks: (IUCLID)

Theoretical oxygen 1,500 mg/g demand Remarks: (Lit.)

Ratio BOD/ThBOD 76 %

Remarks: Closed Bottle test(IUCLID)

### 12.3 Bioaccumulative potential

Bioaccumulation Cyprinus carpio (Carp) - 72 d

at 20 °C - 5 mg/l(Methanol)

Bioconcentration factor (BCF): 1.0

## 12.4 Mobility in soil

Will not adsorb on soil.

#### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

## 12.6 Endocrine disrupting properties

No data available

# 12.7 Other adverse effects

Additional ecological Avoid release to the environment.


information

Stability in water at 19 °C83 - 91 % - 72 h

Remarks: Hydrolyzes on contact with water. Hydrolyzes readily.

- 2.2 yr

Remarks: reaction with hydroxyl radicals(IUCLID)



## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

### **Product**

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

# **SECTION 14: Transport information**

DOT (US)

UN number: 1230 Class: 3 Packing group: II

Proper shipping name: Methanol Reportable Quantity (RQ): 5000 lbs

Poison Inhalation Hazard: No

**IMDG** 

UN number: 1230 Class: 3 (6.1) Packing group: II EMS-No: F-E, S-D

Proper shipping name: METHANOL

**IATA** 

UN number: 1230 Class: 3 (6.1) Packing group: II

Proper shipping name: Methanol

## **SECTION 15: Regulatory information**

## **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Methanol	67-56-1	5000	5000

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

# SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 313** : The following components are subject to reporting

levels established by SARA Title III, Section 313:

Methanol 67-56-1 >= 90 - <= 100 %

**US State Regulations** 

**Massachusetts Right To Know** 

Methanol 67-56-1

Pennsylvania Right To Know

Methanol 67-56-1

Millipore - MX0488

<u> 1illipore</u>

Page 13 of 14

## **Maine Chemicals of High Concern**

Product does not contain any listed chemicals

### **Vermont Chemicals of High Concern**

Product does not contain any listed chemicals

### **Washington Chemicals of High Concern**

Product does not contain any listed chemicals

## California Prop. 65

WARNING: This product can expose you to chemicals including Methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

### The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

#### **TSCA list**

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

#### **SECTION 16: Other information**

#### **Further information**

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 8.15 Revision Date: 08/07/2024 Print Date: 08/08/2024

