

SAFETY DATA SHEET

according to the OSHA
Hazard Communication Standard

Version 6.23
Revision Date 08/12/2026
Print Date 08/12/2026

SECTION 1. IDENTIFICATION

1.1 Product identifiers

Product name : Xylenes

Product Number : 247642

Brand : SIGALD

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

Restrictions on use : Not Available

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
SPRUCE ST 3050
63103 St. Louis

Telephone : (314) 771-5765
Telefax: (800) 325-5052

1.4 Emergency telephone number

Emergency Phone # : 800 424 9300 (CHEMTREC) 24/7
+1 703 527 3887 (CHEMTREC) 24/7

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Hazards for the product as supplied

Flammable liquids : Category 3

Acute toxicity
(Inhalation) : Category 4

SIGALD - 247642

Page 1 of 21

Acute toxicity (Dermal)	: Category 4
Skin irritation	: Category 2
Eye irritation	: Category 2A
Specific target organ toxicity - single exposure	: Category 3 (Respiratory system)
Specific target organ toxicity - repeated exposure	: Category 2 (hearing organs)
Specific target organ toxicity - repeated exposure (Inhalation)	: Category 2 (Central nervous system, Liver, Kidney)
Aspiration hazard	: Category 1
Short-term (acute) aquatic hazard	: Category 2
Long-term (chronic) aquatic hazard	: Category 3

Other hazards

None known.

GHS label elements

Hazard pictograms : 

Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 + H332 Harmful in contact with skin or if inhaled.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H373 May cause damage to organs (hearing organs) through prolonged or repeated exposure.
H373 May cause damage to organs (Central nervous system, Liver, Kidney) through prolonged or repeated exposure if inhaled.
H401 Toxic to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 Get medical advice/ attention if you feel unwell.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

CAS-No. : Not Assigned

SIGALD - 247642

Page 3 of 21

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Xylene	1330-20-7*	$\geq 65 - \leq 85$	TSC
ethylbenzene	100-41-4*	$\geq 10 - \leq 30$	TSC

* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice	: Show this safety data sheet to the doctor in attendance.
If inhaled	: After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.
In case of skin contact	: In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.
In case of eye contact	: After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.
If swallowed	: After swallowing: caution if victim vomits. Risk of aspiration! Keep airways free. Pulmonary failure possible after aspiration of vomit. Call a physician immediately.
Most important symptoms and effects, both acute and delayed	: The most important known symptoms and effects are described in the labelling (see section 2 GHS label elements) and/or in section 11
Protection of first-aiders	: For personal protection see section 8.
Notes to physician	: No data available

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Carbon dioxide (CO ₂) Foam Dry powder
------------------------------	---

Unsuitable extinguishing media	: For this substance/mixture no limitations of extinguishing agents are given.
Specific hazards during fire fighting	: Combustible.
	Vapours are heavier than air and may spread along floors.
	Forms explosive mixtures with air at elevated temperatures.
	Development of hazardous combustion gases or vapours possible in the event of fire.
Hazardous combustion products	: Carbon oxides
Specific extinguishing methods	: No data available
Further information	: Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.
Special protective equipment for fire-fighters	: Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Advice for non-emergency personnel: Do not breathe vapours, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. Advice for emergency responders: Wear appropriate personal protective equipment, as indicated in Section 8.
---	--

Environmental precautions	: Do not let product enter drains. Risk of explosion.
Methods and materials for containment and cleaning up	: Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

SECTION 7. HANDLING AND STORAGE

For precautions see section 2 GHS label elements

Advice on protection against fire and explosion	: Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.
Advice on safe handling	: Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.
Further information on storage conditions	: Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.
Storage class	: 3, Flammable liquids
Recommended storage temperature	: Recommended storage temperature if relevant, see product label.
Packaging material	: Suitable material: Any Metal Drum, Amber Glass Bottle/Jar

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Xylene	1330-20-7	TWA	100 ppm 435 mg/m ³	OSHA Z-1
		TWA	20 ppm	ACGIH
		TWA	2 ppm	US WEEL
		STEL	5 ppm	US WEEL
ethylbenzene	100-41-4	TWA	100 ppm 435 mg/m ³	NIOSH REL

SIGALD - 247642

Page 6 of 21

		ST	125 ppm 545 mg/m ³	NIOSH REL
		TWA	100 ppm 435 mg/m ³	OSHA Z-1

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Xylene	1330-20-7	Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	0.3 g/g creatinine	ACGIH BEI
ethylbenzene	100-41-4	Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	150 mg/g creatinine	ACGIH BEI

Engineering measures : No data available

Personal protective equipment

Respiratory protection : required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Recommended Filter type: : Filter A (acc. to DIN 3181) for vapours of organic compounds

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Hand protection

SIGALD - 247642

Page 7 of 21

Material : Viton®
Break through time : 480 min
Glove thickness : 0.7 mm
Protective index : Splash contact
Manufacturer : Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Material : Viton®
Break through time : 480 min
Glove thickness : 0.7 mm
Protective index : Full contact
Manufacturer : Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Remarks : This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Eye protection : Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).
Safety glasses

Skin and body protection : Flame retardant antistatic protective clothing.

Hygiene measures : Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : colourless

Odour : No data available

Odour Threshold : No data available

pH : substance/mixture is non-polar/aprotic

Melting point/ range : -11 °F / -24 °C

Boiling point/boiling range : 279 - 284 °F / 137 - 140 °C
Method: lit.

Flash point	: 77 °F / 25 °C
	Method: closed cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Flammability (liquids)	: No data available
Burning rate	: No data available
Self-ignition	: 865 °F / 463 °C 1,013 hPa
Upper explosion limit / Upper flammability limit	: 7.0 %(V)
Lower explosion limit / Lower flammability limit	: 1.1 %(V)
Vapour pressure	: 23.99 hPa (99.86 °F / 37.70 °C)
Relative vapour density	: 3.67 (Air = 1.0)
Relative density	: No data available
Density	: 0.86 g/mL (77 °F / 25 °C) Method: lit.
Solubility(ies)	
Water solubility	: 0.1705 g/l partly soluble (77 °F / 25 °C)
Partition coefficient: n- octanol/water	: log Pow: 3.12 (68 °F / 20 °C) Bioaccumulation is not expected.
Autoignition temperature	: 865 °F / 463 °C (1,013 hPa)
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: 0.76 mPa.s (77.00 °F / 25.00 °C)
Viscosity, kinematic	: No data available
Flow time	: No data available
Explosive properties	: Not classified as explosive.
Oxidizing properties	: none

SIGALD - 247642

Page 9 of 21

Molecular weight : 106.17 g/mol

Particle characteristics

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Vapour/air-mixtures are explosive at intense warming.
Chemical stability	: The product is chemically stable under standard ambient conditions (room temperature) .
Possibility of hazardous reactions	: Exothermic reaction with: Strong oxidizing agents Acids sulfur conc. sulfuric acid Risk of explosion/exothermic reaction with: Nitric acid uranium hexafluoride
Conditions to avoid	: Heating.
Incompatible materials	: No data available
Hazardous decomposition products	: For Hazardous combustion products in the event of fire: see section 5

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Mixture

Acute toxicity

Oral: No data available

Acute toxicity estimate Inhalation - 4 h - 12.25 mg/l - vapour(Calculation method)

Symptoms: Possible symptoms:, mucosal irritations, Cough, Shortness of breath, Possible damages:, damage of respiratory tract

Dermal: No data available

Acute toxicity estimate Dermal - 1,467 mg/kg
(Calculation method)

Skin corrosion/irritation

Remarks: Mixture causes skin irritation.

Serious eye damage/eye irritation

Remarks: Mixture causes serious eye irritation.

Respiratory or skin sensitization

No data available

SIGALD - 247642

Page 10 of 21

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: 2B - Group 2B: Possibly carcinogenic to humans (ethylbenzene)

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available
Aspiration hazard, Aspiration may cause pulmonary oedema and pneumonitis.

11.2 Additional Information

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence

Components**Xylene****Acute toxicity**

LD50 Oral - Rat - male - 3,523 mg/kg

(EC Directive 92/69/EEC B.1 Acute Toxicity (Oral))

Remarks: (ECHA)

LC50 Inhalation - Rat - male - 4 h - 29.09 mg/l - vapour

(Regulation (EC) No. 440/2008, Annex, B.2)

Remarks: (Regulation (EC) No 1272/2008, Annex VI)

LD50 Dermal - Rabbit - > 1,700 mg/kg

Remarks: (RTECS)

No data available

Skin corrosion/irritation

Skin - Rabbit

Result: Moderate skin irritation - 24 h

Remarks: (IUCLID)

Remarks: Drying-out effect resulting in rough and chapped skin.

After long-term exposure to the chemical:

Dermatitis

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Causes serious eye irritation. - 24 h

Remarks: (RTECS)

Respiratory or skin sensitization

Local lymph node assay (LLNA) - Mouse

Result: negative

(OECD Test Guideline 429)

Germ cell mutagenicity

Test Type: Mutagenicity (mammal cell test): chromosome aberration.

Test system: Chinese hamster ovary cells

Result: negative

Remarks: (National Toxicology Program)

Test Type: Ames test

Test system: Salmonella typhimurium

Result: negative

Test Type: sister chromatid exchange assay

Test system: Chinese hamster ovary cells

Result: negative

Method: OECD Test Guideline 478

Species: Mouse - male and female

Result: negative

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

May cause respiratory irritation. - Respiratory system

Specific target organ toxicity - repeated exposure

Inhalation - May cause damage to organs through prolonged or repeated exposure.

- Central nervous system, Liver, Kidney

Aspiration hazard

May be fatal if swallowed and enters airways.

ethylbenzene

Acute toxicity

LD50 Oral - Rat - male and female - 3,500 mg/kg

Remarks: (ECHA)

LC50 Inhalation - Rat - male - 4 h - 17.8 mg/l - vapour

Remarks: (ECHA)

LD50 Dermal - Rabbit - 15,433 mg/kg

Remarks: (RTECS)

Skin corrosion/irritation

Skin - Rabbit

Result: Moderate skin irritation - 24 h

Remarks: (ECHA)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Mild eye irritation

SIGALD - 247642

Page 12 of 21

Remarks: (ECHA)

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

Test Type: Chromosome aberration test in vitro

Test system: Chinese hamster ovary cells

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Result: negative

Method: OECD Test Guideline 474

Species: Mouse - male - Bone marrow

Result: negative

Method: OECD Test Guideline 486

Species: Mouse - male and female

Result: negative

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

- hearing organs

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Aspiration hazard

Aspiration may cause pulmonary oedema and pneumonitis.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : Remarks: No data available

Components:

Xylene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2.60 mg/l
End point: mortality
Exposure time: 96 h
Test Type: static test
Analytical monitoring: yes
Method: OECD Test Guideline 203

SIGALD - 247642

Page 13 of 21

Toxicity to algae/aquatic plants	: EC50 (<i>Pseudokirchneriella subcapitata</i>): 4.36 mg/l Exposure time: 73 h Test Type: static test Analytical monitoring: yes Method: OECD Test Guideline 201 GLP: yes
Toxicity to fish (Chronic toxicity)	: NOEC (<i>Oncorhynchus mykiss</i> (rainbow trout)): > 1.3 mg/l End point: mortality Exposure time: 56 d Test Type: flow-through test Analytical monitoring: yes Remarks: (ECHA)
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (<i>Ceriodaphnia dubia</i> (water flea)): 0.96 mg/l End point: reproduction rate Exposure time: 7 d Analytical monitoring: yes Method: US-EPA
Toxicity to microorganisms	: NOEC (activated sludge): 16.2 mg/l Exposure time: 28 h Test Type: static test GLP: yes Remarks: (ECHA)

ethylbenzene:

Toxicity to fish	: LC50 (<i>Oncorhynchus mykiss</i> (rainbow trout)): 4.2 mg/l End point: mortality Exposure time: 96 h Test Type: semi-static test Analytical monitoring: yes Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (<i>Daphnia magna</i> (Water flea)): 1.8 - 2.4 mg/l Exposure time: 48 h Test Type: static test Analytical monitoring: yes Method: US-EPA
Toxicity to algae/aquatic plants	: EC50 (<i>Pseudokirchneriella subcapitata</i> (green algae)): 3.6 mg/l Exposure time: 96 h Test Type: static test Analytical monitoring: yes Method: US-EPA GLP: yes

Toxicity to microorganisms : EC50 (Photobacterium phosphoreum): 9.68 mg/l
Exposure time: 30 min
Remarks: (IUCLID)

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Components:

Xylene:

Biodegradability : aerobic
Inoculum: activated sludge
Concentration: 16 mg/l
Result: Readily biodegradable.
Biodegradation: 94 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
GLP: yes

ethylbenzene:

Biodegradability : aerobic
Inoculum: activated sludge
Concentration: 22 mg/l
Result: Readily biodegradable.
Biodegradation: ca. 79 %
Exposure time: 28 d
Method: ISO 14593
GLP: yes

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Components:

Xylene:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)
Bioconcentration factor (BCF): 7.4 - 18.5
Exposure time: 56 d
Temperature: 50 °F / 10 °C
Concentration: 1.3 mg/l

Partition coefficient: n-octanol/water : log Pow: 3.12 (68 °F / 20 °C)
pH: 7
Remarks: Bioaccumulation is not expected.

ethylbenzene:

Bioaccumulation : Remarks: Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected.

Partition coefficient: n-octanol/water : log Pow: 3.6 (68 °F / 20 °C)
pH: 7.84
Method: Regulation (EC) No. 440/2008, Annex, A.8
GLP: yes
Remarks: Bioaccumulation is not expected.

Mobility in soil

Product:

Stability in soil : Remarks: No data available

Components:

ethylbenzene:

Distribution among environmental compartments : Adsorption/Soil
Koc: 204, log Koc: 2.31
Method: (experimental)
Remarks: Moderately mobile in soils (Lit.)

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Components:

Xylene:

Results of PBT and vPvB assessment : Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII.

Endocrine disrupting properties

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1993
Proper shipping name : Flammable liquid, n.o.s.
(Xylene, ethylbenzene)
Class : 3
Packing group : III
Labels : Class 3 - Flammable liquids
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(Xylene, ethylbenzene)
Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number : UN 1993
Proper shipping name : Flammable liquids, n.o.s.
(Xylene, ethylbenzene)
Class : 3

Packing group : III
Labels : Class 3 - Flammable liquids
ERG Code : 128
Marine pollutant : no

SIGALD - 247642

Page 17 of 21

Poison Inhalation Hazard : No

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Xylene	1330-20-7	100	133
Xylene	1330-20-7	100	100 (F003)
ethylbenzene	100-41-4	100	100 (F003)

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Fire Hazard
Acute Health Hazard
Chronic Health Hazard

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Xylene	1330-20-7	>= 70 - < 90 %
ethylbenzene	100-41-4	>= 20 - < 30 %

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B). The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

Xylene	1330-20-7	>= 70 - < 90 %
ethylbenzene	100-41-4	>= 20 - < 30 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

Xylene	1330-20-7	>= 70 - < 90 %
ethylbenzene	100-41-4	>= 20 - < 30 %

Clean Water Act

The following Hazardous Substances are listed under the U.S. Clean Water Act, Section 311, Table 116.4A:

Xylene	1330-20-7	>= 70 - < 90 %
ethylbenzene	100-41-4	>= 20 - < 30 %

The following Hazardous Chemicals are listed under the U.S. Clean Water Act, Section 311, Table 117.3:

Xylene	1330-20-7	>= 70 - < 90 %
ethylbenzene	100-41-4	>= 20 - < 30 %

This product contains the following toxic pollutants listed under the U.S. Clean Water Act Section 307

ethylbenzene	100-41-4	>= 20 - < 30 %
--------------	----------	----------------

This product contains the following priority pollutants related to the U.S. Clean Water Act:

ethylbenzene	100-41-4	>= 20 - < 30 %
--------------	----------	----------------

US State Regulations

Massachusetts Right To Know

Xylene	1330-20-7
ethylbenzene	100-41-4

Pennsylvania Right To Know

Xylene	1330-20-7
ethylbenzene	100-41-4

Maine Chemicals of High Concern

Product does not contain any listed chemicals

Vermont Chemicals of High Concern

ethylbenzene	100-41-4
--------------	----------

Washington Chemicals of High Concern

ethylbenzene	100-41-4
--------------	----------

California Prop. 65

WARNING: This product can expose you to chemicals including ethylbenzene, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov. **The components of this product are reported in the following inventories:**

US TSCA : All substances listed as active on the TSCA inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants

SIGALD - 247642

Page 19 of 21

The life science business of Merck KGaA, Darmstadt, Germany operates as MilliporeSigma in the US and Canada

**MILLIPORE
SIGMA**

US WEEL	: USA. Workplace Environmental Exposure Levels (WEEL)
ACGIH / TWA	: 8-hour, time-weighted average
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	: 8-hour time weighted average
US WEEL / TWA	: 8-hr TWA
US WEEL / STEL	: Short-Term TWA

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); LSPN - List of Hazardous Notified Substances (Chile); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above

product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.
Copyright 2025 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

Revision Date : 08/12/2026

US / EN