

SAFETY DATA SHEET

according to the OSHA
Hazard Communication Standard

Version 6.22
Revision Date 07/09/2026
Print Date 07/10/2026

SECTION 1. IDENTIFICATION

1.1 Product identifiers

Product name : Dichloromethane

Product Number : 320269
Brand : SIGALD
Index-No. : 602-004-00-3
CAS-No. : 75-09-2

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

Restrictions on use : After February 3, 2025, this chemical substance (as defined in TSCA section 3(2))/product cannot be distributed in commerce to retailers. After January 28, 2026, this chemical substance (as defined in TSCA section 3(2))/product is and can only be distributed in commerce or processed with a concentration of methylene chloride equal to or greater than 0.1% by weight for the following purposes: (1) Processing as a reactant; (2) Processing for incorporation into a formulation, mixture, or reaction product; (3) Processing for repackaging; (4) Processing for recycling; (5) Industrial or commercial use as a laboratory chemical; (6) Industrial or commercial use as a bonding agent for solvent welding; (7) Industrial and commercial use as a paint and coating remover from safety critical, corrosion-sensitive components of aircraft and spacecraft; (8) Industrial and commercial use as a processing aid; (9) Industrial and commercial use for plastic and rubber products manufacturing; (10) Industrial and commercial use as a solvent that becomes part of a formulation or mixture, where that formulation or mixture will be used inside a manufacturing process, and the solvent (methylene chloride) will be reclaimed; (11) Industrial and commercial use in the refinishing for wooden furniture, decorative pieces, and architectural fixtures of artistic, cultural or historic value until May 8, 2029; (12) Industrial and commercial use in adhesives and sealants in aircraft, space vehicle, and turbine applications for structural and safety critical non-structural applications until May 8, 2029; (13) Disposal;

SIGALD - 320269

Page 1 of 18

and (14) Export. The product is being supplied under the TSCA R&D Exemption (40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by MilliporeSigma.

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 SPRUCE ST
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone number

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-527-3887 CHEMTREC (International) 24 Hours/day; 7 Days/week

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Hazards for the product as supplied

Skin irritation : Category 2

Eye irritation : Category 2A

Carcinogenicity : Category 2

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

Other hazards

None known.

GHS label elements

Hazard pictograms :  

Signal word : Warning

Hazard statements : H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.

Precautionary statements :

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P261 Avoid breathing mist or vapours.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

CAS-No. : 75-09-2

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Dichloromethane	75-09-2*	>= 80 - <= 100	TSC

* Indicates that the identifier is a CAS No.

SECTION 4. FIRST AID MEASURES

General advice	: Show this safety data sheet to the doctor in attendance.
If inhaled	: After inhalation: fresh air. Call in physician.
In case of skin contact	: In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.
In case of eye contact	: After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.
If swallowed	: After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.
Most important symptoms and effects, both acute and delayed	: The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
Protection of first-aiders	: For personal protection see section 8.
Notes to physician	: No data available

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Water Foam Carbon dioxide (CO ₂) Dry powder
Unsuitable extinguishing media	: For this substance/mixture no limitations of extinguishing agents are given.
Specific hazards during fire fighting	: Combustible. Development of hazardous combustion gases or vapours possible in the event of fire.
Hazardous combustion	: Carbon oxides

products

Hydrogen chloride gas

Specific extinguishing methods : No data available

Further information : Suppress (knock down) gases/vapours/mists with a water spray jet.
Prevent fire extinguishing water from contaminating surface water or the ground water system.

Special protective equipment for fire-fighters : Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Advice for non-emergency personnel:
Do not breathe vapours, aerosols.
Avoid substance contact.
Ensure adequate ventilation.
Evacuate the danger area, observe emergency procedures, consult an expert.
Advice for emergency responders:
For personal protection see section 8.

Environmental precautions : Do not let product enter drains.

Methods and materials for containment and cleaning up : Cover drains. Collect, bind, and pump off spills.
Observe possible material restrictions (see sections 7 and 10).
Take up with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

SECTION 7. HANDLING AND STORAGE

For precautions see section 2.2.

Advice on safe handling : Work under hood. Do not inhale substance/mixture.
Avoid generation of vapours/aerosols.

Further information on storage conditions : Tightly closed.
Keep in a well-ventilated place.
Keep locked up or in an area accessible only to

qualified or authorised persons.

Storage class : 6.1D, Non-combustible, acute toxic Cat.3 / toxic hazardous materials or hazardous materials causing chronic effects

Recommended storage temperature : Recommended storage temperature see product label.

Further information on storage stability : Heat sensitive.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Dichloromethane	75-09-2	TWA	50 ppm	ACGIH
		PEL	25 ppm	OSHA CARC
		STEL	125 ppm	OSHA CARC
		ECEL-TWA	2 ppm 8 mg/m ³	TSCA ECEL
		EPA STEL	16 ppm 57 mg/m ³	TSCA ECEL

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Dichloromethane	75-09-2	Dichloromethane	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/l	ACGIH BEI

Engineering measures : No data available

Personal protective equipment

Respiratory protection : required when vapours/aerosols are generated.

Recommended Filter : Filter AX (EN 371)
type:

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Hand protection

Material : Viton®
Break through time : 120 min
Glove thickness : 0.7 mm
Protective index : Splash contact
Manufacturer : Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Remarks : This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Eye protection : Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).
Safety glasses

Skin and body protection : protective clothing

Hygiene measures : Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : colourless

Odour : ether-like

Odour Threshold : 250 ppm

pH : No data available

Melting point/ range	: -139 °F / -95 °C (1,013 hPa)
Boiling point/boiling range	: 103.6 - 104 °F / 39.8 - 40 °C Method: lit.
Flash point	: does not flash
Evaporation rate	: 0.71
Burning rate	: No data available
Self-ignition	: 1121 °F / 605 °C 1,013 hPa Method: DIN 51794
Upper explosion limit / Upper flammability limit	: Upper explosion limit 22 %(V)
Lower explosion limit / Lower flammability limit	: Lower explosion limit 13 %(V)
Vapour pressure	: 584 hPa (77 °F / 25 °C)
Relative vapour density	: 2.93
Relative density	: No data available
Density	: 1.325 g/mL (77 °F / 25 °C) Method: lit.
Solubility(ies) Water solubility	: 13.2 g/l (77 °F / 25 °C) pH: 7
Partition coefficient: n- octanol/water	: log Pow: 1.25 (68 °F / 20 °C) pH: 7 Method: (experimental) Bioaccumulation is not expected.
Autoignition temperature	: 1033.0 °F / 556.1 °C
Decomposition temperature	: No data available
Viscosity Viscosity, dynamic	: 0.42 mPa.s (77 °F / 25 °C)
Viscosity, kinematic	: No data available
Flow time	: No data available

Explosive properties	: Not classified as explosive.
Oxidizing properties	: none
Refractive index	: 1.42 (68 °F / 20 °C) 589.3 nm
Molecular weight	: 84.93 g/mol
Particle characteristics	
Particle size	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No data available
Chemical stability	: The product is chemically stable under standard ambient conditions (room temperature) .
Contains the following stabiliser(s):	: 2-methyl-2-butene (0.005 %)
Possibility of hazardous reactions	: Risk of explosion with: Alkali metals nitrogen oxides nitrogen dioxide Potassium sodium azide perchloric acid Nitric acid aluminium chloride Amines Oxygen (as liquefied gas) powdered aluminium sodium aromatic hydrocarbons with powdered aluminium Exothermic reaction with: Alkaline earth metals Powdered metals amides alcoholates nonmetallic oxides potassium tert-butanolate sodium amide Lithium
Conditions to avoid	: no information available

Incompatible materials : No data available

Hazardous decomposition : In the event of fire: see section 5 products

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

Acute toxicity estimate Oral - 2,500 mg/kg
(Calculation method)
LD50 Oral - Rat - male and female - > 2,000 mg/kg
(OECD Test Guideline 401)
LC50 Inhalation - Mouse - 4 h - 86 mg/l - vapour

Remarks: (ECHA)

Symptoms: Possible damages:, mucosal irritations

Acute toxicity estimate Dermal - 2,500 mg/kg
(Calculation method)
LD50 Dermal - Rat - male and female - > 2,000 mg/kg
(OECD Test Guideline 402)

Skin corrosion/irritation

Skin - Rabbit

Result: Irritations - 4 h
(OECD Test Guideline 404)

Remarks: Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Eye irritation

Remarks: (ECHA)

Remarks: Risk of corneal clouding.

Respiratory or skin sensitization

Local lymph node assay (LLNA) - Mouse

Result: negative
(OECD Test Guideline 429)

Germ cell mutagenicity

Test Type: Mutagenicity (mammal cell test): chromosome aberration.

Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: positive

Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: positive

Test Type: In vivo micronucleus test

Species: Mouse

SIGALD - 320269

Page 10 of 18

Cell type: Bone marrow
Application Route: Gavage
Method: OECD Test Guideline 474
Result: negative

Carcinogenicity

Suspected of causing cancer.

IARC: 2A - Group 2A: Probably carcinogenic to humans (Dichloromethane)

NTP: RAHC - Reasonably anticipated to be a human carcinogen (Dichloromethane)

OSHA: OSHA specifically regulated carcinogen (Dichloromethane)

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Inhalation - May cause drowsiness or dizziness. - Central nervous system

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

Repeated dose toxicity - Rat - male and female - Oral - 104 Weeks - No observed adverse effect level - 6 mg/kg

Repeated dose toxicity - Rat - male and female - Inhalation - 104 Weeks

RTECS: PA8050000

Dizziness, Nausea, Vomiting, narcosis, Cough, irritant effects, Unconsciousness, Shortness of breath, respiratory paralysis, somnolence, depressed respiration, CNS disorders, inebriation

Risk of corneal clouding.

The following applies to aliphatic halogenated hydrocarbons in general: systemic effect: narcosis, cardiovascular disorders. Toxic effect on liver, kidneys.

Dichloromethane is metabolized in the body producing carbon monoxide which increases and sustains carboxyhemoglobin levels in the blood, reducing the oxygen-carrying capacity of the blood.

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Systemic effects:

After absorption of large quantities:

CNS disorders

Drowsiness

Dizziness

drop in blood pressure

Cardiac irregularities

depressed respiration

inebriation

SIGALD - 320269

Page 11 of 18

Unconsciousness
narcosis

Swallowing may result in damage to the following:

Liver
Kidney

The following applies to aliphatic halogenated hydrocarbons in general: systemic effect: narcosis, cardiovascular disorders. Toxic effect on liver, kidneys.

Other dangerous properties can not be excluded.

This substance should be handled with particular care.

Stomach - Irregularities - Based on Human Evidence

Stomach - Irregularities - Based on Human Evidence

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Dichloromethane:

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): 193.00 mg/l End point: mortality Exposure time: 96 h Test Type: flow-through test Analytical monitoring: yes Remarks: (ECHA)
Toxicity to daphnia and other aquatic invertebrates	: LC50 (Daphnia magna (Water flea)): 27 mg/l End point: mortality Exposure time: 48 h Test Type: static test Method: US-EPA
Toxicity to fish (Chronic toxicity)	: LC50 (Pimephales promelas (fathead minnow)): 471 mg/l End point: mortality Exposure time: 8 d Test Type: flow-through test Analytical monitoring: yes Remarks: (ECHA)
Toxicity to	: EC50 (activated sludge): 2,590 mg/l

SIGALD - 320269

Page 12 of 18

microorganisms

Exposure time: 40 min
Test Type: static test
Analytical monitoring: yes
Method: OECD Test Guideline 209

Persistence and degradability

Components:

Dichloromethane:

Biodegradability : aerobic
Inoculum: activated sludge, non-adapted
Concentration: 5 mg/l
Result: Readily biodegradable.
Biodegradation: 68 %
Exposure time: 28 d
Method: OECD Test Guideline 301D
GLP: yes

Bioaccumulative potential

Components:

Dichloromethane:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 2 - 5.4
Exposure time: 6 Weeks
Concentration: 250 µg/l
Method: OECD Test Guideline 305
GLP: yes

Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 6 - 40
Exposure time: 6 Weeks
Concentration: 25 µg/l
Method: OECD Test Guideline 305
GLP: yes

Partition coefficient: n-octanol/water : log Pow: 1.25 (68 °F / 20 °C)
pH: 7
Method: (experimental)
Remarks: Bioaccumulation is not expected.

Mobility in soil

No data available

Other adverse effects

Components:

Dichloromethane:

Results of PBT and vPvB assessment : Not persistent, bioaccumulative, and toxic (PBT). Not very persistent and very bioaccumulative (vPvB).

SIGALD - 320269

Page 13 of 18

: Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII.

Endocrine disrupting properties

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1593
Proper shipping name : Dichloromethane
Class : 6.1
Packing group : III
Labels : Division 6.1 - Toxic substances
Packing instruction (cargo : 663
aircraft)
Packing instruction : 655
(passenger aircraft)

IMDG-Code

UN number : UN 1593
Proper shipping name : DICHLOROMETHANE

Class : 6.1
Packing group : III
Labels : 6.1
EmS Code : F-A, S-A
Marine pollutant : no

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number : UN 1593
Proper shipping name : Dichloromethane

Class : 6.1

SIGALD - 320269

Page 14 of 18

Packing group	: III
Labels	: Division 6.1 - Toxic substances
ERG Code	: 160
Marine pollutant	: no
Poison Inhalation Hazard	: No

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Dichloromethane	75-09-2	1000	1000

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Acute Health Hazard
Chronic Health Hazard

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Dichloromethane	75-09-2	>= 90 - <= 100 %
-----------------	---------	------------------

US State Regulations

Massachusetts Right To Know

Dichloromethane	75-09-2
-----------------	---------

Pennsylvania Right To Know

Dichloromethane	75-09-2
-----------------	---------

Maine Chemicals of High Concern

Product does not contain any listed chemicals

Vermont Chemicals of High Concern

Dichloromethane	75-09-2
-----------------	---------

Washington Chemicals of High Concern

Dichloromethane	75-09-2
-----------------	---------

California Prop. 65

WARNING: This product can expose you to chemicals including Dichloromethane, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov. **The components of this product are reported in the following inventories:**

US TSCA : All substances listed as active on the TSCA inventory

TSCA list

No substances are subject to a Significant New Use Rule.

After February 3, 2025, this chemical substance (as defined in TSCA section 3(2))/product cannot be distributed in commerce to retailers. After January 28, 2026, this chemical substance (as defined in TSCA section 3(2))/product is and can only be distributed in commerce or processed with a concentration of methylene chloride equal to or greater than 0.1% by weight for the following purposes: (1) Processing as a reactant; (2) Processing for incorporation into a formulation, mixture, or reaction product; (3) Processing for repackaging; (4) Processing for recycling; (5) Industrial or commercial use as a laboratory chemical; (6) Industrial or commercial use as a bonding agent for solvent welding; (7) Industrial and commercial use as a paint and coating remover from safety critical, corrosion-sensitive components of aircraft and spacecraft; (8) Industrial and commercial use as a processing aid; (9) Industrial and commercial use for plastic and rubber products manufacturing; (10) Industrial and commercial use as a solvent that becomes part of a formulation or mixture, where that formulation or mixture will be used inside a manufacturing process, and the solvent (methylene chloride) will be reclaimed; (11) Industrial and commercial use in the refinishing for wooden furniture, decorative pieces, and architectural fixtures of artistic, cultural or historic value until May 8, 2029; (12) Industrial and commercial use in adhesives and sealants in aircraft, space vehicle, and turbine applications for structural and safety critical non-structural applications until May 8, 2029; (13) Disposal; and (14) Export.

The following substance(s) is/are subject to TSCA 12(b) export notification requirements:
Dichloromethane 75-09-2

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
OSHA CARC	: OSHA Specifically Regulated Chemicals/Carcinogens
TSCA ECEL	: TSCA Existing Chemical Exposure Limit
ACGIH / TWA	: 8-hour, time-weighted average
OSHA CARC / PEL	: Permissible exposure limit (PEL)
OSHA CARC / STEL	: Excursion limit
TSCA ECEL / ECEL-TWA	: Existing Chemical Exposure List (TWA)
TSCA ECEL / EPA STEL	: EPA STEL

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - SIGALD - 320269

Page 16 of 18

Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2025 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

Revision Date : 07/09/2026

US / EN

