

SAFETY DATA SHEET

according to the OSHA
Hazard Communication Standard

Version 6.11
Revision Date 07/14/2026
Print Date 07/15/2026

SECTION 1. IDENTIFICATION

1.1 Product identifiers

Product name : Economy Water Vapor Trap Refill

Product Number : 23989
Brand : Supelco

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

Restrictions on use : The product is being supplied under the TSCA R&D Exemption (40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by MilliporeSigma.

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 SPRUCE ST
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone number

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-
527-3887 CHEMTREC (International) 24
Hours/day; 7 Days/week

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Hazards for the product as supplied

Skin corrosion : Category 1B

Serious eye damage : Category 1

Carcinogenicity : Category 1B

Specific target organ toxicity - repeated exposure (Inhalation) : Category 1 (Lungs)

Other hazards

None known.

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.
H350 May cause cancer.
H372 Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

CAS-No. : Not Assigned

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
silicon dioxide	7631-86-9*	$\geq 50 - < 70$	-
aluminum oxide	1344-28-1*	$\geq 50 - < 70$	-
Disodium oxide	1313-59-3*	$\geq 20 - < 30$	-
Magnesium oxide	1309-48-4*	$\geq 10 - < 20$	-
Quartz, respirable	14808-60-7*	$\geq 5 - < 10$	-

* Indicates that the identifier is a CAS No.

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : First aiders need to protect themselves.
Show this safety data sheet to the doctor in attendance.

If inhaled : After inhalation: fresh air. Call in physician.

In case of skin contact : In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.
Call a physician immediately.

In case of eye contact : After eye contact: rinse out with plenty of water.
Immediately call in ophthalmologist.
Remove contact lenses.

If swallowed : After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation).
Call a physician immediately.
Do not attempt to neutralise.

Most important symptoms and effects, both acute and delayed	: The most important known symptoms and effects are described in the labelling (see section 2 GHS label elements) and/or in section 11
Protection of first-aiders	: For personal protection see section 8.
Notes to physician	: No data available

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	: For this substance/mixture no limitations of extinguishing agents are given.
Specific hazards during fire fighting	: Not combustible. Ambient fire may liberate hazardous vapours.
Hazardous combustion products	: Sodium oxides Magnesium oxide Aluminum oxide silicon oxides
Hazardous combustion products	: Sodium oxides Magnesium oxide Aluminum oxide silicon oxides
Specific extinguishing methods	: No data available

Further information	: Suppress (knock down) gases/vapours/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.
Special protective equipment for fire-fighters	: Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Advice for non-emergency personnel: Avoid generation and inhalation of dusts in all circumstances. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert. Advice for emergency responders: Wear appropriate personal protective equipment, as indicated in Section 8.
Environmental precautions	: Do not let product enter drains.
Methods and materials for containment and cleaning up	: Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully. Dispose of properly. Clean up affected area. Avoid generation of dusts.

SECTION 7. HANDLING AND STORAGE

For precautions see section 2 GHS label elements

Advice on safe handling	: Work under hood. Do not inhale substance/mixture.
Further information on storage conditions	: Tightly closed. Dry. Keep in a well-ventilated place. Keep locked up or in an area accessible only to qualified or authorised persons.

Storage class : 6.1D, Non-combustible, acute toxic Cat.3 / toxic hazardous materials or hazardous materials causing chronic effects

Recommended storage temperature : Recommended storage temperature see product label.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
silicon dioxide	7631-86-9	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m3 / %SiO2 (Silica)	OSHA Z-3
		PEL (respirable)	0.05 mg/m3	OSHA CARC
		TWA	6 mg/m3 (Silica)	NIOSH REL
aluminum oxide	1344-28-1	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Respirable particulate matter)	1 mg/m3 (Aluminium)	ACGIH
Magnesium oxide	1309-48-4	TWA (Inhalable particulate matter)	10 mg/m3	ACGIH
		TWA (fume, total particulate)	15 mg/m3	OSHA Z-1
Quartz, respirable	14808-60-7	TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (Respirable)	0.025 mg/m3 (Silica)	ACGIH

		particulate matter)		
		PEL (respirable)	0.05 mg/m3	OSHA CARC
		TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL

Engineering measures : No data available

Personal protective equipment

Respiratory protection : required when dusts are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Recommended Filter type: : Filter type P3

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Hand protection

Material : Nitrile rubber
Break through time : 480 min
Glove thickness : 0.11 mm
Protective index : Full contact
Manufacturer : KCL 741 Dermatril® L

Material : Nitrile rubber
Break through time : 480 min
Glove thickness : 0.11 mm
Protective index : Splash contact
Manufacturer : KCL 741 Dermatril® L

Remarks : Handle with impervious gloves.
This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the

supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

- Eye protection : Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).
Tightly fitting safety goggles
- Skin and body protection : protective clothing
- Hygiene measures : Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : solid
- Colour : No data available
- Odour : No data available
- Odour Threshold : No data available
pH : No data available
- Melting point : No data available
- Boiling point/boiling range : No data available
- Flash point : Not applicable
- Evaporation rate : No data available
- Flammability (solid, gas) : The product is not flammable.
- Flammability (liquids) : No data available
- Burning rate : No data available
- Self-ignition : Not applicable
- Upper explosion limit /
Upper flammability limit : Not applicable
- Lower explosion limit /
Lower flammability limit : Not applicable
- Vapour pressure : No data available
- Relative vapour density : No data available

Relative density	: No data available
Density	: No data available
Water solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: Not applicable
Decomposition temperature	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Flow time	: No data available
Explosive properties	: Not classified as explosive.
Oxidizing properties	: none
Particle characteristics	
Particle size	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No data available
Chemical stability	: The product is chemically stable under standard ambient conditions (room temperature) .
Possibility of hazardous reactions	: No data available
Conditions to avoid	: no information available
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: In the event of fire: see section 5

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Mixture

Acute toxicity

Oral: No data available

Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages: damage of respiratory tract

Dermal: No data available

Skin corrosion/irritation

Remarks: Mixture causes burns.

Serious eye damage/eye irritation

Remarks: Mixture causes serious eye damage.

Risk of blindness!

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

Possible carcinogen.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: OSHA specifically regulated carcinogen (silicon dioxide)

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens. (Quartz, respirable)

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

Mixture causes damage to organs through prolonged or repeated exposure.

- Lungs

Aspiration hazard

No data available

11.2 Additional Information

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Other dangerous properties can not be excluded.

This substance should be handled with particular care.

Handle in accordance with good industrial hygiene and safety practice.

Stomach - Irregularities - Based on Human Evidence

Liver - Irregularities - Based on Human Evidence

Components

silicon dioxide

Acute toxicity

LD50 Oral - Rat - male and female - > 5,000 mg/kg

(OECD Test Guideline 401)

LC50 Inhalation - Rat - male and female - 4 h - > 5.01 mg/l - aerosol

(OECD Test Guideline 436)

LD50 Dermal - Rabbit - > 5,000 mg/kg

Remarks: (ECHA)

No data available

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 4 h

(OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation - 24 h

(OECD Test Guideline 405)

Respiratory or skin sensitization

in vivo assay - Guinea pig

Result: Not a skin sensitizer.

(OECD Test Guideline 406)

Germ cell mutagenicity

Test Type: Ames test

Test system: Salmonella typhimurium

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster ovary cells

Result: negative

Test Type: Chromosome aberration test in vitro

Test system: Chinese hamster ovary cells

Result: negative

Species: Rat - male

Result: negative

Remarks: (ECHA)

Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

aluminum oxide**Acute toxicity**

LD50 Oral - Rat - male and female - > 10,000 mg/kg

(OECD Test Guideline 401)

LC50 Inhalation - Rat - male and female - 4 h - > 2.3 mg/l - aerosol

(OECD Test Guideline 403)

Dermal: No data available

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 24 h

(OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation

(OECD Test Guideline 405)

Respiratory or skin sensitization

Draize Test - Guinea pig

Result: Does not cause skin sensitisation.

- Mouse

Result: Does not cause respiratory sensitisation.

Germ cell mutagenicity

Test Type: Ames test

Test system: Bacillus subtilis

Result: negative

Remarks: (IUCLID)

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Disodium oxide

Acute toxicity

Oral: No data available
Inhalation: No data available
Dermal: No data available
No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

Remarks: No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available
No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Magnesium oxide

Acute toxicity

Oral: No data available
Inhalation: No data available
Dermal: No data available

Skin corrosion/irritation

Remarks: No data available

Serious eye damage/eye irritation

Remarks: No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Quartz, respirable**Acute toxicity**

Oral: No data available

Inhalation: No data available

Dermal: No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC:	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
NTP:	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
OSHA:	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

Inhalation - Causes damage to organs through prolonged or repeated exposure.

- Lungs

Aspiration hazard

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

silicon dioxide:

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): > 5,000 mg/l End point: mortality Exposure time: 96 h Test Type: static test Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 5,000 mg/l Test Type: static test Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: ErC50 (Desmodesmus subspicatus (green algae)): > 173.1 mg/l Test Type: static test Analytical monitoring: yes Method: OECD Test Guideline 201 GLP: yes
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 68 mg/l End point: mortality Test Type: semi-static test Analytical monitoring: yes Method: OECD Test Guideline 211 GLP: yes
Toxicity to microorganisms	: EC50 (activated sludge): > 1,000 mg/l Exposure time: 3 h Test Type: static test Method: OECD Test Guideline 209 GLP: yes

Disodium oxide:

Toxicity to fish	: Remarks: No data available
------------------	------------------------------

Persistence and degradability

Components:

silicon dioxide:

Biodegradability	: Remarks: The methods for determining biodegradability are not applicable to inorganic substances.
------------------	---

aluminum oxide:

Biodegradability : Remarks: The methods for determining the biological degradability are not applicable to inorganic substances.

Disodium oxide:

Biodegradability : Remarks: No data available

Magnesium oxide:

Biodegradability : Remarks: The methods for determining biodegradability are not applicable to inorganic substances.

Quartz, respirable:

Biodegradability : Remarks: The methods for determining the biological degradability are not applicable to inorganic substances.

Bioaccumulative potential

Components:

silicon dioxide:

Partition coefficient: n-octanol/water : Remarks: Not applicable for inorganic substances

aluminum oxide:

Partition coefficient: n-octanol/water : Remarks: Not applicable for inorganic substances

Disodium oxide:

Bioaccumulation : Remarks: No data available

Magnesium oxide:

Partition coefficient: n-octanol/water : Remarks: Not applicable for inorganic substances

Quartz, respirable:

Partition coefficient: n-octanol/water : Remarks: Not applicable for inorganic substances

Mobility in soil

Components:

Disodium oxide:

Stability in soil : Remarks: No data available

Other adverse effects

Components:

silicon dioxide:

Additional ecological information : No ecological problems are to be expected when the product is handled and used with due care and attention.

aluminum oxide:

Additional ecological information : No ecological problems are to be expected when the product is handled and used with due care and attention.

Disodium oxide:

Additional ecological information : No data available

Endocrine disrupting properties

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 3262
Proper shipping name : Corrosive solid, basic, inorganic, n.o.s.
(Disodium oxide)
Class : 8
Packing group : II
Labels : Class 8 - Corrosive substances
Packing instruction (cargo : 863
aircraft)
Packing instruction : 859
(passenger aircraft)

IMDG-Code

UN number : UN 3262
Proper shipping name : CORROSIVE SOLID, BASIC, INORGANIC, N.O.S.
(Disodium oxide)

Class : 8
 Packing group : II
 Labels : 8
 EmS Code : F-A, S-B
 Marine pollutant : no

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number : UN 3262
 Proper shipping name : Corrosive solid, basic, inorganic, n.o.s.
 (Disodium oxide)
 Class : 8
 Packing group : II
 Labels : Class 8 - Corrosive substances
 ERG Code : 154
 Marine pollutant : no
 Poison Inhalation Hazard : No

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Acute Health Hazard
 Chronic Health Hazard

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

aluminum oxide	1344-28-1	>= 50 - < 70 %
----------------	-----------	----------------

US State Regulations

Massachusetts Right To Know

silicon dioxide

7631-86-9

Supelco - 23989

Page 18 of 20

aluminum oxide	1344-28-1
Magnesium oxide	1309-48-4

Pennsylvania Right To Know

aluminum oxide	1344-28-1
Magnesium oxide	1309-48-4
Quartz, respirable	14808-60-7

Maine Chemicals of High Concern

Quartz, respirable	14808-60-7
--------------------	------------

Vermont Chemicals of High Concern

Product does not contain any listed chemicals

Washington Chemicals of High Concern

Product does not contain any listed chemicals

The components of this product are reported in the following inventories:

US TSCA : All substances listed as active on the TSCA inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA CARC	: OSHA Specifically Regulated Chemicals/Carcinogens
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	: USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	: 8-hour, time-weighted average
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA CARC / PEL	: Permissible exposure limit (PEL)
OSHA Z-1 / TWA	: 8-hour time weighted average
OSHA Z-3 / TWA	: 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide;

GHS - Globally Harmonised System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2025 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

Revision Date : 07/14/2026

US / EN