

SAFETY DATA SHEET

Version 6.35
Revision Date 08/12/2025
Print Date 08/13/2025

SECTION 1. IDENTIFICATION

1.1 Product identifiers

Product name : 50 COMP INDOOR AIR STD, 3X1ML,
100UG/ML, MEOH:H2O (95:5)

Product Number : 4M9148-U
Brand : Supelco

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

Uses advised against : The product is being supplied under the TSCA R&D Exemption (40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by MilliporeSigma.

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 SPRUCE ST
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone number

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-
527-3887 CHEMTREC (International) 24
Hours/day; 7 Days/week

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 2

Acute toxicity (Oral) : Category 3

Acute toxicity (Inhalation) : Category 3

Acute toxicity (Dermal) : Category 3

Specific target organ toxicity - single exposure : Category 1 (Eyes, Central nervous system)

Other hazards

None known.

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapour.
H301 + H311 + H331 Toxic if swallowed, in contact with skin or if inhaled.
H370 Causes damage to organs (Eyes, Central nervous system).

Precautionary statements : **Prevention:**
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P310 + P330 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. Rinse mouth.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P311 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a

POISON CENTER/ doctor.
P307 + P311 IF exposed: Call a POISON CENTER or doctor/ physician.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Methanol	67-56-1*	>= 90 - <= 100	-

* Indicates that the identifier is a CAS No.
Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : First aiders need to protect themselves.
Show this safety data sheet to the doctor in attendance.

If inhaled : After inhalation: fresh air. Immediately call in physician.
If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact : In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.
Call a physician immediately.

In case of eye contact : After eye contact: rinse out with plenty of water.
Call in ophthalmologist.
Remove contact lenses.

If swallowed	: After swallowing: fresh air. Make victim drink ethanol (e.g. 1 drinking glass of a 40% alcoholic beverage). Call a doctor immediately (mention methanol ingestion). Only in exceptional cases, if no medical care is available within one hour, induce vomiting (only in fully conscious persons) and make victim drink ethanol again (approx. 0.3 ml of a 40% alcoholic beverage/kg body weight/hour).
Most important symptoms and effects, both acute and delayed	: The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
Protection of first-aiders	: For personal protection see section 8.
Notes to physician	: No data available

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Foam Carbon dioxide (CO ₂) Dry powder
Unsuitable extinguishing media	: For this substance/mixture no limitations of extinguishing agents are given.
Specific hazards during fire fighting	: Combustible.

Pay attention to flashback.

Vapours are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

Hazardous combustion products	: Carbon oxides
-------------------------------	-----------------

Specific extinguishing methods	: No data available
Further information	: Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.
Special protective equipment for fire-fighters	: Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Advice for non-emergency personnel: Do not breathe vapours, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. Advice for emergency responders: For personal protection see section 8.
Environmental precautions	: Do not let product enter drains. Risk of explosion.
Methods and materials for containment and cleaning up	: Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

SECTION 7. HANDLING AND STORAGE

For precautions see section 2.2.

Advice on protection against fire and explosion	: Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.
Advice on safe handling	: Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.
Further information on storage conditions	: Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Keep locked up or in an area accessible only to qualified or authorised persons.

Storage class : 3, Flammable liquids

Recommended storage temperature : -13 - 14 °F / -25 - -10 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		ST	250 ppm 325 mg/m ³	NIOSH REL
		TWA	200 ppm 260 mg/m ³	NIOSH REL
		TWA	200 ppm 260 mg/m ³	OSHA Z-1

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Methanol	67-56-1	Methanol	Urine	End of shift (As soon as possible after exposure ceases)	15 mg/l	ACGIH BEI

Engineering measures : No data available

Personal protective equipment

Respiratory protection : required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Recommended Filter : Filter type ABEK
type:

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Hand protection

Remarks : required

Eye protection : Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).
Safety glasses

Skin and body protection : Flame retardant antistatic protective clothing.

Hygiene measures : Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : No data available

Odor : No data available

Odor Threshold : No data available
pH : No data available

Melting point : No data available
: 149 °F / 65 °C (97 hPa)

Flash point : 49.5 °F / 9.7 °C
(10 hPa)
Method: Regulation (EC) No. 440/2008, Annex, A.9,
closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Flammability (liquids)	: No data available
Burning rate	: No data available
Upper explosion limit / Upper flammability limit	: 36.5 %(V)
Lower explosion limit / Lower flammability limit	: 6 %(V)
Vapor pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available
Density	: No data available
Water solubility	: No data available
Partition coefficient: n- octanol/water	: No data available
Autoignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Flow time	: No data available
Explosive properties	: Not classified as explosive.
Oxidizing properties	: none
Particle characteristics Particle size	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Vapours may form explosive mixture with air.
Chemical stability	: The product is chemically stable under standard ambient conditions (room temperature) .
Possibility of hazardous reactions	: No data available

Conditions to avoid : Warming.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition : In the event of fire: see section 5 products

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Mixture

Acute toxicity

Acute toxicity estimate Oral - 105.9 mg/kg

(Calculation method)

Acute toxicity estimate Inhalation - 4 h - 3.28 mg/l - vapour (Calculation method)

Acute toxicity estimate Dermal - 317.5 mg/kg

(Calculation method)

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Mixture causes damage to organs. - Eyes, Central nervous system

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

Components

Methanol

Acute toxicity

Acute toxicity estimate Oral - 100.1 mg/kg

(Expert judgement)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Symptoms: Nausea, Vomiting

Acute toxicity estimate Inhalation - 4 h - 3.1 mg/l - vapour

(Expert judgement)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Symptoms: Irritation symptoms in the respiratory tract.

Acute toxicity estimate Dermal - 300.1 mg/kg

(Expert judgement)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation

Remarks: (ECHA)

Remarks: Drying-out effect resulting in rough and chapped skin.

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation

Remarks: (ECHA)

Respiratory or skin sensitization

Sensitisation test: - Guinea pig

Result: negative

(OECD Test Guideline 406)

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Test Type: Ames test

Test system: Salmonella typhimurium

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster lung cells

Result: negative

Method: OECD Test Guideline 474

Species: Mouse - male and female - Bone marrow

Result: negative

Carcinogenicity

Did not show carcinogenic effects in animal experiments.

Reproductive toxicity

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

Causes damage to organs. - Eyes, Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Acute oral toxicity - Nausea, Vomiting

Acute inhalation toxicity - Irritation symptoms in the respiratory tract.

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Methanol:

Toxicity to fish	: LC50 (<i>Lepomis macrochirus</i> (Bluegill)): 15,400.0 mg/l End point: mortality Exposure time: 96 h Test Type: flow-through test Analytical monitoring: yes Method: US-EPA
Toxicity to daphnia and other aquatic invertebrates	: EC50 (<i>Daphnia magna</i> (Water flea)): 18,260 mg/l End point: Immobilization Exposure time: 96 h Test Type: semi-static test Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: ErC50 (<i>Pseudokirchneriella subcapitata</i> (green algae)): ca. 22,000.0 mg/l Exposure time: 96 h Test Type: static test Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	: NOEC (<i>Oryzias latipes</i> (Orange-red killifish)): 7,900 mg/l Exposure time: 200 h Remarks: (External MSDS)
Toxicity to	: IC50 (activated sludge): > 1,000 mg/l

microorganisms

Exposure time: 3 h
Test Type: static test
Analytical monitoring: yes
Method: OECD Test Guideline 209

Persistence and degradability

Components:

Methanol:

Biodegradability	:	Result: Readily biodegradable. Biodegradation: 99 % Exposure time: 30 d Method: OECD Test Guideline 301D
Biochemical Oxygen Demand (BOD)	:	600 - 1,120 mg/g Incubation time: 5 d Remarks: (IUCLID)
Chemical Oxygen Demand (COD)	:	1,420 mg/g Remarks: (IUCLID)
ThOD	:	1,500 mg/g Remarks: (Lit.)
BOD/ThOD	:	76 % Remarks: Closed Bottle test (IUCLID)
Stability in water	:	Hydrolysis: 83 - 91 % at 19 °C(72 h) Remarks: Hydrolyses on contact with water. Hydrolyses readily. Degradation half life: 2.2 yr Remarks: reaction with hydroxyl radicals (IUCLID)
Photodegradation	:	Degradation (direct photolysis): 50 % Degradation half life: 17.2 d

Bioaccumulative potential

Components:

Methanol:

Bioaccumulation	:	Species: Cyprinus carpio (Carp) Bioconcentration factor (BCF): 1.0 Exposure time: 72 d Temperature: 68 °F / 20 °C Concentration: 5 mg/l
Partition coefficient: n-	:	log Pow: -0.77 (77 °F / 25 °C)

octanol/water

Method: (experimental)
Remarks: (HSDB)
Bioaccumulation is not expected.

Mobility in soil

Components:

Methanol:

Stability in soil : Remarks: Will not adsorb on soil.

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Components:

Methanol:

Results of PBT and vPvB assessment : Not persistent, bioaccumulative, and toxic (PBT).

Additional ecological information : Avoid release to the environment.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1230
Proper shipping name : Methanol solution
Class : 3
Subsidiary risk : 6.1
Packing group : II

Supelco - 4M9148-U

Page 13 of 19

Labels : Class 3 - Flammable liquids, Division 6.1 - Toxic substances

Packing instruction (cargo aircraft) : 364

Packing instruction (passenger aircraft) : 352

IMDG-Code

UN number : UN 1230

Proper shipping name : METHANOL SOLUTION

Class : 3

Subsidiary risk : 6.1

Packing group : II

Labels : 3 (6.1)

EmS Code : F-E, S-D

Marine pollutant : no

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

National Regulations

49 CFR Road

UN/ID/NA number : UN 1230

Proper shipping name : Methanol SOLUTION

Class : 3

Packing group : II

Labels : Class 3 - Flammable liquids

ERG Code : 131

Marine pollutant : no

Poison Inhalation Hazard : No

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
benzene	71-43-2	10	10 (D018)
ethylbenzene	100-41-4	100	100 (F003)
n-butanol	71-36-3	100	100 (F003)
1,4-dichlorobenzene	106-46-7	100	100 (D027)
1,2-Dichloroethane	107-06-2	100	100 (D028)
Chloroform	67-66-3	10	10 (D022)

Tetrachlorethylene	127-18-4	100	100 (D039)
Tetrachlorethylene	127-18-4	10	10 (F001)
Tetrachlorethylene	127-18-4	10	10 (F002)
trichloroethylene	79-01-6	100	100 (D040)
Ethyl Methyl Ketone	78-93-3	5000	5000 (D035)
Ethyl Methyl Ketone	78-93-3	100	100 (F005)

SARA 304 Extremely Hazardous Substances Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 : Fire Hazard
Hazards

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Methanol 67-56-1 >= 90 - <= 100 %

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B). The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

Methanol 67-56-1 >= 90 - <= 100 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

Methanol 67-56-1 >= 90 - <= 100 %

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

Toluene	108-88-3	>= 0 - < 0.1 %
benzene	71-43-2	>= 0 - < 0.1 %
p-xylene	106-42-3	>= 0 - < 0.1 %
m-xylene	108-38-3	>= 0 - < 0.1 %
o-xylene	95-47-6	>= 0 - < 0.1 %
ethylbenzene	100-41-4	>= 0 - < 0.1 %
1,4-dichlorobenzene	106-46-7	>= 0 - < 0.1 %
styrene	100-42-5	>= 0 - < 0.1 %
1,2-Dichloroethane	107-06-2	>= 0 - < 0.1 %
1,2-Dichloropropane	78-87-5	>= 0 - < 0.1 %
Chloroform	67-66-3	>= 0 - < 0.1 %
trichloroethylene	79-01-6	>= 0 - < 0.1 %
n-Butylacetate	123-86-4	>= 0 - < 0.1 %

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

Toluene	108-88-3	>= 0 - < 0.1 %
benzene	71-43-2	>= 0 - < 0.1 %
ethylbenzene	100-41-4	>= 0 - < 0.1 %
styrene	100-42-5	>= 0 - < 0.1 %
1,2-Dichloroethane	107-06-2	>= 0 - < 0.1 %
Chloroform	67-66-3	>= 0 - < 0.1 %
trichloroethylene	79-01-6	>= 0 - < 0.1 %
n-Butylacetate	123-86-4	>= 0 - < 0.1 %

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

Methanol	67-56-1
water	7732-18-5
Dichloromethane	75-09-2
benzene	71-43-2
1,4-dichlorobenzene	106-46-7
styrene	100-42-5
1,2-Dichloroethane	107-06-2
Chloroform	67-66-3
Tetrachlorethylene	127-18-4
Bromodichloromethane	75-27-4
trichloroethylene	79-01-6

Pennsylvania Right To Know

Methanol	67-56-1
Dichloromethane	75-09-2
acetone	67-64-1
Toluene	108-88-3
benzene	71-43-2
p-xylene	106-42-3
m-xylene	108-38-3
o-xylene	95-47-6
ethylbenzene	100-41-4
1,4-dichlorobenzene	106-46-7
styrene	100-42-5
1,2-Dichloroethane	107-06-2
1,2-Dichloropropane	78-87-5
Chloroform	67-66-3
Tetrachlorethylene	127-18-4
Bromodichloromethane	75-27-4
1,2,4-Trimethylbenzene	95-63-6
trichloroethylene	79-01-6
Chlorodibromomethane	124-48-1
ethyl acetate	141-78-6
2-Propanol	67-63-0
n-butanol	71-36-3
Ethyl Methyl Ketone	78-93-3
4-methylpentan-2-one	108-10-1
n-Butylacetate	123-86-4

Maine Chemicals of High Concern

water	7732-18-5
Toluene	108-88-3
benzene	71-43-2
styrene	100-42-5
mesitylene	108-67-8

Vermont Chemicals of High Concern

water	7732-18-5
Dichloromethane	75-09-2
Toluene	108-88-3
benzene	71-43-2
ethylbenzene	100-41-4
styrene	100-42-5
mesitylene	108-67-8
Tetrachlorethylene	127-18-4
Ethyl Methyl Ketone	78-93-3

Washington Chemicals of High Concern

water	7732-18-5
Dichloromethane	75-09-2
Toluene	108-88-3
benzene	71-43-2
ethylbenzene	100-41-4
styrene	100-42-5
mesitylene	108-67-8
Tetrachlorethylene	127-18-4
Ethyl Methyl Ketone	78-93-3

California Prop. 65

WARNING: This product can expose you to chemicals including Dichloromethane, benzene, ethylbenzene, 1,4-dichlorobenzene, styrene, 1,2-Dichloroethane, 1,2-Dichloropropane, Chloroform, Tetrachlorethylene, Bromodichloromethane, trichloroethylene, 4-methylpentan-2-one, which is/are known to the State of California to cause cancer, and Methanol, n-Hexane, Toluene, benzene, Chloroform, trichloroethylene, 4-methylpentan-2-one, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA : Product contains substance(s) not listed on TSCA inventory.

TSCA list

The following substance(s) is/are subject to a Significant New Use Rule:

trichloroethylene	79-01-6	See 40 CFR § 721.10851; Final Rule
-------------------	---------	------------------------------------

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	: 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2025 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

Revision Date : 08/12/2025

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

US / EN