

SAFETY DATA SHEET

according to the OSHA
Hazard Communication Standard

Version 7.12
Revision Date 07/21/2026
Print Date 07/22/2026

SECTION 1. IDENTIFICATION

1.1 Product identifiers

Product name : LpDNPH Rezorian™ Cartridge

Product Number : 54075-U

Brand : Supelco

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

Restrictions on use : Not Available

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 SPRUCE ST
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765

Fax : +1 800 325-5052

1.4 Emergency telephone number

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-
527-3887 CHEMTREC (International) 24
Hours/day; 7 Days/week

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Hazards for the product as supplied

Not a hazardous substance or mixture according to the Globally Harmonised System (GHS).

Other hazards

None known.

GHS label elements

Not a hazardous substance or mixture according to the Globally Harmonised System (GHS).

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

CAS-No. : 231-545-4

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
silicon dioxide	7631-86-9*	$\geq 90 - \leq 100$	-
2,4-Dinitrophenylhydrazine	119-26-6*	$\geq 1 - < 5$	-
ethanol	64-17-5*	$\geq 0.1 - < 1$	-

* Indicates that the identifier is a CAS No.

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled : After inhalation: fresh air.

In case of skin contact : In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

In case of eye contact : After eye contact: rinse out with plenty of water. Remove contact lenses.

If swallowed : After swallowing: make victim drink water (two glasses at most). Consult doctor if feeling unwell.

Most important symptoms and effects, both acute and delayed : The most important known symptoms and effects are described in the labelling (see section 2 GHS label elements) and/or in section 11

Protection of first-aiders : For personal protection see section 8.

Notes to physician : No data available

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water
Foam
Carbon dioxide (CO₂)
Dry powder

Unsuitable extinguishing media	: For this substance/mixture no limitations of extinguishing agents are given.
Specific hazards during fire fighting	: Combustible.
	Development of hazardous combustion gases or vapours possible in the event of fire.
Hazardous combustion products	: Carbon oxides
	Nitrogen oxides (NO _x)
	silicon oxides
Specific extinguishing methods	: No data available
Further information	: Suppress (knock down) gases/vapours/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.
Special protective equipment for fire-fighters	: In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Advice for non-emergency personnel: Avoid inhalation of dusts. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert. Advice for emergency responders: Wear appropriate personal protective equipment, as indicated in Section 8.
Environmental precautions	: Do not let product enter drains.
Methods and materials	: Cover drains. Collect, bind, and pump off spills.

for containment and
cleaning up

Observe possible material restrictions (see sections 7
and 10).
Take up dry. Dispose of properly. Clean up affected
area. Avoid generation of dusts.

SECTION 7. HANDLING AND STORAGE

For precautions see section 2 GHS label elements

Further information on storage conditions : Tightly closed.
Dry.

Storage class : 11, Combustible Solids

Recommended storage temperature : 36 - 46 °F / 2 - 8 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
silicon dioxide	7631-86-9	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m ³ / %SiO ₂ (Silica)	OSHA Z-3
		PEL (respirable)	0.05 mg/m ³	OSHA CARC
		TWA	6 mg/m ³ (Silica)	NIOSH REL
ethanol	64-17-5	TWA	1,000 ppm 1,900 mg/m ³	OSHA Z-1
		STEL	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,900 mg/m ³	NIOSH REL

Engineering measures : No data available

Personal protective equipment

Respiratory protection : required when dusts are generated.

Our recommendations on filtering respiratory

protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Recommended Filter type: : Filter type P2

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Hand protection

Material : Nitrile rubber
Break through time : 480 min
Glove thickness : 0.11 mm
Protective index : Full contact
Manufacturer : KCL 741 Dermatril® L

Material : Nitrile rubber
Break through time : 480 min
Glove thickness : 0.11 mm
Protective index : Splash contact
Manufacturer : KCL 741 Dermatril® L

Remarks : Handle with impervious gloves.
This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Eye protection : Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).
Safety glasses

Hygiene measures : Change contaminated clothing. Wash hands after working with substance.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Beads

Supelco - 54075-U

Page 5 of 14

Colour	: white
Odour	: odourless
Odour Threshold	: Not applicable
pH	: ca. 6 Concentration: 50 g/l
Melting point	: No data available
Boiling point/boiling range	: No data available
Flash point	: Not applicable
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Flammability (liquids)	: No data available
Burning rate	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available
Density	: ca. 2 g/cm ³ (68 °F / 20 °C)
Solubility(ies) Water solubility	: 0.001 g/l (68 °F / 20 °C)
Partition coefficient: n- octanol/water	: Not applicable for inorganic substances
Autoignition temperature	: No data available
Decomposition temperature	: > 3,632 °F / > 2,000 °C
Viscosity, dynamic	: No data available

Supelco - 54075-U

Page 6 of 14

Viscosity, kinematic	: No data available
Flow time	: No data available
Explosive properties	: No data available
Oxidizing properties	: none
Particle characteristics	
Particle size	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: The following applies in general to flammable organic substances and mixtures: in correspondingly fine distribution, when whirled up a dust explosion potential may generally be assumed.
Chemical stability	: The product is chemically stable under standard ambient conditions (room temperature) .
Possibility of hazardous reactions	: Stable under recommended storage conditions.
Conditions to avoid	: no information available
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: For Hazardous combustion products in the event of fire: see section 5

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

Acute toxicity estimate Oral - > 5,000 mg/kg
(Calculation method)
Inhalation: No data available
Dermal: No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

Supelco - 54075-U

Page 7 of 14

No data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: OSHA specifically regulated carcinogen (silicon dioxide)

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

Stomach - Irregularities - Based on Human Evidence

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

silicon dioxide:

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): > 5,000 mg/l End point: mortality Exposure time: 96 h Test Type: static test Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 5,000 mg/l Test Type: static test Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: ErC50 (Desmodesmus subspicatus (green algae)): > 173.1 mg/l Test Type: static test Analytical monitoring: yes Method: OECD Test Guideline 201 GLP: yes
Toxicity to daphnia and other aquatic	: NOEC (Daphnia magna (Water flea)): 68 mg/l End point: mortality

Supelco - 54075-U

Page 8 of 14

invertebrates (Chronic toxicity)	Test Type: semi-static test Analytical monitoring: yes Method: OECD Test Guideline 211 GLP: yes
Toxicity to microorganisms	: EC50 (activated sludge): > 1,000 mg/l Exposure time: 3 h Test Type: static test Method: OECD Test Guideline 209 GLP: yes

ethanol:

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): 15,300 mg/l End point: mortality Exposure time: 96 h Test Type: flow-through test Analytical monitoring: yes Method: US-EPA
Toxicity to daphnia and other aquatic invertebrates	: LC50 (Ceriodaphnia dubia (water flea)): 5,012 mg/l End point: mortality Exposure time: 48 h Test Type: static test Remarks: (ECHA)
Toxicity to algae/aquatic plants	: ErC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l Exposure time: 72 h Test Type: static test Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	: NOEC (Danio rerio (zebra fish)): 250 mg/l Exposure time: 120 h Test Type: semi-static test Remarks: (ECHA)
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 9.6 mg/l End point: reproduction rate Exposure time: 9 d Test Type: semi-static test Remarks: (ECHA)
Toxicity to microorganisms	: IC50 (activated sludge): > 1,000 mg/l Exposure time: 3 h Test Type: static test Analytical monitoring: yes Method: OECD Test Guideline 209 The value is given in analogy to the following substances: Methanol

Persistence and degradability

Components:

silicon dioxide:

Biodegradability : Remarks: The methods for determining biodegradability are not applicable to inorganic substances.

ethanol:

Biodegradability : aerobic
Inoculum: activated sludge, non-adapted
Result: Readily biodegradable.
Biodegradation: ca. 95 %
Exposure time: 15 d
Method: OECD Test Guideline 301E

Biochemical Oxygen Demand (BOD) : 930 - 1,670 mg/g
Incubation time: 5 d
Remarks: (Lit.)

ThOD : 2,100 mg/g
Remarks: (Lit.)

Bioaccumulative potential

Components:

silicon dioxide:

Partition coefficient: n-octanol/water : Remarks: Not applicable for inorganic substances

ethanol:

Bioaccumulation : Remarks: Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected.

Partition coefficient: n-octanol/water : log Pow: -0.35 (75 °F / 24 °C)
pH: 7.4
Method: OECD Test Guideline 107
Remarks: Bioaccumulation is not expected.

Mobility in soil

No data available

Other adverse effects

Components:

silicon dioxide:

Additional ecological information : No ecological problems are to be expected when the product is handled and used with due care and

attention.

ethanol:

Results of PBT and vPvB assessment : Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII.

Endocrine disrupting properties

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good
Poison Inhalation Hazard : No

Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Hydrochloric Acid	7647-01-0	5000	

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Chronic Health Hazard

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Massachusetts Right To Know

synthetic amorphous silica, pptd. 112926-00-8

Massachusetts Right To Know

silicon dioxide 7631-86-9
Hydrochloric Acid 7647-01-0

Pennsylvania Right To Know

synthetic amorphous silica, pptd. 112926-00-8

Pennsylvania Right To Know

Hydrochloric Acid 7647-01-0

Maine Chemicals of High Concern

water 7732-18-5

Vermont Chemicals of High Concern

water 7732-18-5

Washington Chemicals of High Concern

water 7732-18-5

New Jersey Right To Know

synthetic amorphous silica, pptd. 112926-00-8

California Prop. 65

WARNING: This product can expose you to chemicals including ethanol, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. **The components of this product are reported in the following inventories:**

US TSCA : All substances listed as active on the TSCA inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA CARC	: OSHA Specifically Regulated Chemicals/Carcinogens
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	: USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / STEL	: Short-term exposure limit
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA CARC / PEL	: Permissible exposure limit (PEL)
OSHA Z-1 / TWA	: 8-hour time weighted average
OSHA Z-3 / TWA	: 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United

States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2025 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

Revision Date : 07/21/2026

US / EN